



TCP is proud to have been awarded ENERGY STAR® Partner of the Year 2010.

TCP is committed to providing high quality CFLs that are the benchmark in energy efficiency. Our compact fluorescent light bulbs use 75% less energy than standard incandescent bulbs and last up to 10 times longer.

However, to have lamps ENERGY STAR qualified, they have to pass several test criteria. For example, all ENERGY STAR qualified lamps must be designated by a specific color temperature; 2700K, 3000K, 4100K, etc., consumers typically relate these color temperatures to words like warm white, bright white or cool white. These lamps must fall within a 7-step ANSI MacAdam ellipse for that color temperature, which ensures color consistency in the manufacturing process.

In addition to the technical aspects of bulb testing, the product packaging must tell a true story to the consumer. The packaging of an ENERGY STAR qualified CFL must list numerous components and features of the lamp, and be supported with test data.

By selecting energy saving lighting, you will be working toward reducing your energy bills and significantly reducing greenhouse gases into our atmosphere. TCP's ENERGY STAR qualified CFLs save \$30 or more in electricity costs over the lifetime of each bulb. TCP is proud of our diversified selection of ENERGY STAR qualified CFLs.

All of TCP's CFLs listed on both sides of this sheet have undergone rigorous testing as required by the ENERGY STAR® 4.0 program. In order for a CFL to earn the ENERGY STAR it must pass various photometric, electronic, life performance and packaging tests. New to the ENERGY STAR® 4.0 specification are requirements such as committing to manufacture CFLs with no more than 5mg of mercury in lamps less than 25 watts and 6mg of mercury in lamps 25 watts up to 40 watts. Additionally, reflector lamps intended for indoor qualification must pass elevated temperature lumen maintenance testing, similar to life in a recessed can, a typical application for reflector lamps.

*Material taken from <http://www.energystar.gov/>



	Item Number	Item Description	Unit/Ballast Watts	Incandescent Comparison	Initial Lumens	Rated Life
SpringLight™	801009	9W SpringLight™	9	40	550	10000
	80100935	9W SpringLight™ 35K	9	40	550	10000
	80100950	9W SpringLight™ 50K	9	40	500	10000
	801014	14W SpringLight™	14	60	900	10000
	8010143	14W SpringLight™ 3 pack	14	60	900	10000
	80101435	14W SpringLight™ 35K	14	60	900	10000
	80101441	14W SpringLight™ 41K	14	60	900	10000
	80101450	14W SpringLight™ 50K	14	60	850	10000
	801019	19W SpringLight™	19	75	1200	10000
	8010193	19W SpringLight™ 3 pack	19	75	1200	10000
	80101935	19W SpringLight™ 35K	19	75	1200	10000
	80101941	19W SpringLight™ 41K	19	75	1200	10000
	80101950	19W SpringLight™ 50K	19	75	1200	10000
	801023	23W SpringLight™	23	100	1600	10000
	8010233	23W SpringLight™ 3 pack	23	100	1600	10000
	80102335	23W SpringLight™ 35K	23	100	1600	10000
	80102341	23W SpringLight™ 41K	23	100	1600	10000
	801023413	23W SpringLight™ 41K 3 pack	23	100	1600	10000
	80102350	23W SpringLight™ 50K	23	100	1500	10000
	801027	27W SpringLight™	27	100	1850	10000
	8010273	27W SpringLight™ 3 pack	27	100	1850	10000
	80102735	27W SpringLight™ 35K	27	100	1850	10000
	80102750	27W SpringLight™ 50K	27	100	1750	10000
	80143	14W SpringLight™ Shipper	14	60	900	10000
	8014353	14W SpringLight™ 35K 3 pack Shipper	14	60	800	10000
	80193	19W Shipper SpringLight™	19	75	1200	10000
	802014	14W R20 SpringLight™	14	40	495	8000
	8020142	14W R20 SpringLight™ 2 pack	14	40	495	8000
	80233	23W Shipper SpringLight™	23	100	1600	10000
	8023353	23W Shipper 35K SpringLight™ 3 pack	23	100	1500	10000
	803014	14W R30 SpringLight™	14	65	645	8000
	8030142	14W R30 SpringLight™ 2 pack	14	65	645	8000
	80301435	14W R30 SpringLight™ 35K	14	65	600	8000
	804023	23W R40 SpringLight™	23	120	1250	8000
	805023	23W Par 38 SpringLight™	23	90	1200	8000
	8050232	23W Par 38 SpringLight™ 2 pack	23	90	1200	8000
	8060092	9W G25 SpringLight™ 2 pack	9	40	525	8000
	8060142	14W G25 SpringLight™ 2 pack	14	60	800	8000
	806142	14W G25 Shipper SpringLight™	14	60	800	8000
	8070092	9W A-Lamp SpringLight™ 2 pack	9	40	450	8000
8070142	14W A-Lamp SpringLight™ 2 pack	14	60	800	8000	
807142	14W A-Lamp Shipper SpringLight™	14	60	800	8000	
TCP Pro 	41314	14W A-Lamp InstaBright G2	14	60	800	8000
	4R3014	14W R30 InstaBright G2	14	65	650	8000
	4G2514	14W G25 InstaBright G2	14	60	800	8000
	4890941k	9W Full SpringLamp®	9	40	550	12000



	Item Number	Item Description	Unit/Ballast Watts	Incandescent Comparison	Initial Lumens	Rated Life
TCP Pro NEW!	48913	13W Full SpringLamp®	13	60	900	12000
	4891330k	13W Full SpringLamp® 30K	13	60	925	12000
	4891335k	13W Full SpringLamp® 35K	13	60	850	12000
	4891341k	13W Full SpringLamp® 41K	13	60	850	12000
	48913C	13W Candelabra Full Spring	13	60	900	12000
	48918	18W Full SpringLamp®	18	75	1300	12000
	4891830k	18W Full SpringLamp® 30K	18	75	1200	12000
	4891835k	18W Full SpringLamp® 35K	18	75	1200	12000
	4891841k	18W Full SpringLamp® 41K	18	75	1200	12000
	4891850k	18W Full SpringLamp® 50K	18	75	1200	12000
	48923	23W Full SpringLamp® 27K	23	100	1650	12000
	4T213	13W T2 Full SpringLamp®	13	60	825	12000
	4T223	23W T2 Full SpringLamp®	23	100	1600	12000
	TCP	10120	20W Dimming SpringLamp®	20	75	1100
10123		23W Dimming SpringLamp®	23	100	1500	10000
1070931K		9W Torpedo 31K	9	40	425	8000
11309		9W A-Lamp	9	40	450	8000
11316		16W A-Lamp	16	60	900	8000
1131631K		16W A-Lamp 31K	16	60	900	8000
11319		19W A-Lamp	19	60	1100	8000
11931931K		19W A-Lamp 31K	19	60	1100	8000
18215		15W HPF SpringLamp®	15	60	900	10000
18220		20W HPF SpringLamp®	20	75	1100	10000
19032		14/19/32W 3-Way SpringLamp®	14/19/32	40/75/150	2150	10000
1G2504		4W G25 27K	4	25	250	8000
1G2509		9W G25 27K	9	40	520	8000
1G250931K		9W G25 30K	9	40	520	8000
1G250935K		9W G25 35K	9	40	450	8000
1G250951K		9W G25 51K	9	40	450	8000
1G300941K		9W G30 41K	9	40	500	8000
1G3014		14W G30 27K	14	60	750	8000
1G3019		19W G30 27K	19	75	900	8000
1G301931K		19W G30 31K	19	75	1100	8000
1G4014		14W G40 27K	14	60	800	8000
1G401431K		14W G40 31K	14	60	875	8000
1G4019		19W G40 27K	19	75	1100	8000
1G401931K		19W G40 31K	19	75	1100	8000
1G401935K		19W G40 35K	19	75	1100	8000
1P3816		16W Par 38 27K	16	75	750	8000
1P381631K		16W Par 38 31K	16	75	750	8000
1P381641K		16W Par 38 41K	16	75	750	8000
2P3819		19W Par 38 27K	19	85	1000	8000
2P381941K		19W Par 38 41K	19	85	1000	8000
1P3823		23W Par 38 27K	23	90	1200	8000
1R2009		9W R20 27K	9	25	300	8000
1R2014		14W R20 27K	14	50	500	8000
1R201441K		14W R20 27K	14	50	400	8000
1R4019		19W R40 27K	19	75	950	8000
1R401935K		19W R40 35K	19	75	950	8000
1R4023		23W R40 27K	23	120	1200	8000
1T2004		4W T20 Capsule	4	25	250	8000
1T200451K		4W T20 Capsule 51K	4	25	250	8000
1T2009		9W T20 Capsule	9	40	520	8000
1T200941K		9W T20 Capsule 41K	9	40	550	8000
1T2014		14W T20 Capsule	14	60	800	8000
1T2409		9W T24 Capsule	9	40	495	8000
1T2414		14W T24 Capsule	14	60	900	8000
1T241935K		19W T24 Capsule	19	75	1100	8000
21314		14W A-Lamp	14	60	800	8000
2131431K		14W A-Lamp 31K	14	60	800	8000
2131435K		14W A-Lamp 35K	14	60	800	8000
2131441K		14W A-Lamp 41K	14	60	800	8000
2131465K		14W A-Lamp 65K	14	60	800	8000
28904		4W 27K SpringLamp®	4	25	250	8000
28904T		4W Tall 27k SpringLamp®	4	25	250	8000
28909		9W 27k SpringLamp®	9	40	550	12000
2890951K		9W 50K SpringLamp®	9	40	450	12000
28913		13W 27k SpringLamp®	13	60	900	12000
28914F2		14W Fresh 2	14	60	900	10000
28918		18W 27K SpringLamp®	18	75	1200	12000
2891835K		18W 35K SpringLamp®	18	75	1100	12000
2891850K		18W 50K SpringLamp®	18	75	1100	10000
28923F2		23W Fresh 2	23	100	1600	10000
28923		23W 27k SpringLamp®	23	100	1600	10000
2892335K	23W 35K SpringLamp®	23	100	1500	12000	
2892341K	23W 41K SpringLamp®	23	100	1500	12000	
2892350K	23W 50K SpringLamp®	23	100	1500	10000	
28927M	27W 27K SpringLamp®	27	100	1850	10000	
28927M31K	27W 31K SpringLamp®	27	100	1850	12000	
28927M35K	27W 35K SpringLamp®	27	100	1750	12000	
28930M	30W 27K Mini SpringLamp®	30	125	2000	10000	
28932	32W 27K SpringLamp®	32	120	2100	10000	
28942	42W 27K SpringLamp®	42	150	2700	10000	
28942M	42W 27K Mini SpringLamp®	42	150	2800	10000	
28968	68W 27K SpringLamp®	68	300	4200	10000	
2G2514	14W G25 27K	14	60	800	8000	
2G251435K	14W G25 35K	14	60	800	8000	
2R3014	14W R30 27K	14	65	650	8000	
2R3014 BULK 48	14W R30 Bulk 48	14	65	650	8000	
2R301435K	14W R30 35K	14	65	600	8000	
2R3016	16W R30 27K	16	75	750	8000	
2R3016BULK48	16W R30 Bulk 48	16	75	750	8000	
2R301631K	16W R30 31K	16	75	750	8000	
2R301635K	16W R30 35K	16	75	750	8000	
2R301641K	16W R30 41K	16	75	750	8000	
PF301635K	16W Flat Par 30 35K	16	75	700	8000	
PF301641K	16W Flat Par 30 41K	16	75	700	8000	

TCP is proud to have been awarded
ENERGY STAR® Partner of the Year 2010.



PARTNER OF THE YEAR



TCP Pro R30 InstaBright G2



TCP Pro 13W T2



20W TCP Dimming SpringLamp®



9W G25 TCP 27K



9W R20 TCP 27K



23W R40 TCP 27K



14W A Lamp TCP 27K



4W SpringLamp TCP 27K



27W Mini SpringLamp TCP 27K



23W Par 38 TCP 27K