

For quick, easy, and affordable LED upgrades, switch to TCP's LED Downlights. TCP downlights have both E26 and direct wire options, PMMA plastic to prevent lens discoloration, and quick-snap holding arms to quickly attach to a recessed can. With a traditional look, these downlights provide smooth, even light in the color temperature you need.

Reasons to choose the LED Traditional Selectable Recessed Downlights from TCP

- Color Selectable choose between 2400K/2700K/3000K or 3000K/4000K/5000K
- The 5"/6" models are wattage selectable choose between 8W, 10.5W and 14.5W
- Long, 50,000 hour life minimizes replacement and maintenance costs
- Excellent color consistency and CRI enhances colors of the focal point while maintaining uniformity throughout the lighting installation
- Very low heat generation makes the downlight perfect for sensitive display lighting
- Durable PMMA plastic housing prevents discoloration
- Easy installation mounts directly to either a 4" or 6" recessed can and includes both E26 and direct wire power options
- Smooth, uniform dimming from 100 10%
- 5"/6" features a beveled design

Ideal Applications

CommercialIndustrial

Retail

Residential

Healthcare

Specifications:

 Color Temperatures
 2400K/2700K/3000K or 3000K/4000K/5000K

 Wattage options
 4": 10W

 5"/6": 8W, 10.5W, 14.5W

 Input Line Voltage
 120 VAC

 Input Line Frequency
 50/60HZ

 Lamp Life (Rated)
 50,000 hours

Minimum Starting Temp-22°F/-30°C

Maximum Operating Temp104°F/40°C

CRI80

 $\hbox{IC-rated for direct contact with insulation} \\$

UL approved for damp location (indoor only)—outdoor environment may cause yellowing of the white trim. This is not covered by warranty.









LED Traditional Selectable Recessed Downlight

Specifications:









ITEM #	DESCRIPTION	VOLTAGE	WATTS	INCANDES. WATTS	LPW	LUMENS	COLOR	CRI	MOL (inches)	DIA (inches)	BEAM ANGLE	BASE	ENERGY STAR	WARRANTY YEARS
LED 75W	Equivalent Option:	s												
DR4 Downligh	t • Dimmable • 35,000 H	lour									ı			
L75DR4DCCT1	4" LED Color Selectable Traditional Downlight 2400/2700/3000	120V	10	75	76.5/85/85	765/850/850	2400K/2700K/3000K	80	3.0	5	120°	E26		5
L75DR4DCCT2	4" LED Color Selectable Traditional Downlight 3000/4000/5000	120V	10	75	90/96/91.5	900/960/915	3000K/4000K/5000K	80	3.0	5	120°	E26		5
LED 120W E	quivalent Options													
DR56 Downlig	ht • Dimmable • 35,000	Hour						ı						
L120DR56DCCT1	5"/6" LED Color & Wattage Selectable Traditional Beveled Downlight 2400/2700/3000	120V	8/10.5/14.5	120	8W: 95.6/106.3/106.3	8W: 765/850/850	2400K/2700K/3000K	80	3.0	7.4	120°	E26		
					10.5W: 95.2/104.8/104.8	10.5W: 1000/1100/1100								5
					14.5W: 86.9/96.6/96.6	14.5W: 1260/1400/1400								
L120DR56DCCT2	5"/6" LED Color & Wattage Selectable Traditional Beveled Downlight 3000/4000/5000	120V	8/10.5/14.5	120	8W: 113.8/118.1/115	8W: 910/945/920	3000K/4000K/5000K	80	3.0	7.4	120°			
					10.5W: 104.8/110.5/106.7	10.5W: 1100/1160/1120						E26	*	5
					14.5W: 100/95.5/102.3	14.5W: 1450/1370/1490								
					,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	, , , , , , , ,								



TECHNOLOGY CAST IN A BEAUTIFUL LIGHT

For over 20 years, TCP has been designing, developing and delivering energy-efficient lighting into the market. Thanks to our cutting-edge technology and manufacturing expertise, we have shipped billions of high quality lighting products. With TCP, you can count on a lighting product that is designed to meet the needs of the market - that transforms your surroundings and envelopes you in warmth - lighting that generates beauty with every flip of the switch.

Sales:	Catalog Number:
Date:	Туре:
Model:	Notes:
Project:	OTCP
Rep:	we know light.™