



# T6 Circline Lamp / Adapter Specifications

## T6 Circline Compact Fluorescent

10,000 Hours

### Applications:

Use anywhere a standard incandescent is used.

- + Table Lamps
- + Floor Lamps
- + Ceiling Fixtures




### Special Applications Options (Ordering Suffix):


- 3100°K (31K), 3500°K (35K), 4100°K (41K), 5100°K (51K), 6500°K (65K)

### Features and Benefits


- T6 lamps feature smaller diameters with bright light to fit more applications
- Long life CFL, 10,000 hours average rated life
- Lasts 7 years, based on 4 hours use per day
- Lasts 10-13 times longer than similar incandescent
- Replaceless often, ideal for hard to reach places
- Lower maintenance and labor costs for lamp replacements
- Saves up to 75% in Energy Costs compared to similar light output incandescent lamps
- 2700°K color temperature – closest to incandescent light
- Instant start, flicker free
- Quick run-up time – Instant start, flicker free!
- World class phosphor insures high lumen output and excellent lumen maintenance



17040L



17030/27



17033L  
16533L

Catalog Number


Notes

Type



### Specifications (at full brightness)

End of Life Protection.....	Yes
Bracket Type .....	Bent Wing
Ballast Type .....	Electronic
Starting Method.....	Modified Rapid Start
Input Line Voltage .....	120VAC
Input Line Frequency .....	50/60HZ
Lamp Life (rated) .....	10,000 Hours
Ballast Life (rated) .....	50,000 Hours
Color Temperature .....	2700°K
Color Rendering Index .....	82
Min. Starting Temperature .....	-20 ° F
Max. Operating Temperature .....	160 ° F
U.L. / C.U.L. Listed .....	Yes
FCC Compliance .....	Part 18, Subpart C
Lamp Operating Frequency .....	45 KHZ
Lamp Current Crest Factor .....	< 1.60
Max. Open Circuit Voltage .....	600V

Warranties and Certifications:	Item#	Description	Lamp Wattage	Incandescent Wattage Comparison	Input Line Current	Initial Lumens	MOL (inches)	Diameter (inches)	Power Factor	THD	Ballast Replacement	Lamp Replacement
	 <b>ISO 9002</b> <b>CERTIFIED</b>  <b>15 MONTH</b> <b>WARRANTY</b>	17022/18	T6 Lamp with Ballast	18	75	.30A	1200	3.65	5.75	> .50	< 150%	17022
17030/27		T6 Lamp with Ballast	27	120	.45A	2000	3.65	7.50	> .50	< 150%	17030	32027
17036/32		T6 Lamp with Ballast	32	130	.49A	2200	3.65	9.00	> .50	< 150%	17036	32032
17033L		T6 Lamp with Ballast	33	125	.55A	2000	3.50	5.50	> .50	< 150%	17036	32033
17040L		T6 Lamp with Ballast	40	150	.66A	2800	3.65	7.50	> .50	< 150%	17040	32040
17058L		T6 Lamp with Ballast	58	200	.80A	3700	3.65	9.00	> .50	< 150%	17058	32058
12522/18		T6 Lamp with Ballast	18	75	.20A	1200	3.65	5.75	> .95	< 24%	12522	32018
12530/27		T6 Lamp with Ballast	27	120	.28A	2000	3.65	7.50	> .95	< 24%	12530	32027
12536/32		T6 Lamp with Ballast	32	130	.32A	2200	3.65	9.00	> .95	< 24%	12536	32032
16533L		T6 Lamp with Ballast 3-Way	10/20/33	50/100/150	.55A	2150	3.50	5.50	> .50	< 150%	16533	32033
16550L		T6 Lamp with Ballast 3-Way	22/33/55	90/120/150	.86A	2500	4.75	7.50	> .50	< 150%	16555	32018/32027