



Wet Location A19 A-Lamps

Omni-Directional

The performance you expect from TCP A-Lamps is now available for wet location applications.

Limitless options for the following applications:

- Outdoor Fixtures
- Landscape Lights
- Security Lights

Great features and benefits:

- Energy efficient: Up to 85% more efficient than incandescent alternatives
- UL wet location rated
- Long life: 25,000 hours
- Dimmable
- Similar look and feel as incandescent alternative
- Available in 2700K, 3000K, 4100K and 5000K
- Fits any installation where a standard A19 bulb is used
- Rated for totally enclosed fixtures



Wet Location
Omni-Directional A-Lamp



LED
we know light.™

TCP®

325 Campus Dr. | Aurora, Ohio 44202 | P: 800-324-1496 | tcp.com

©TCP APR 2017 / WF44150





ELITE Series

LED Wet Location A19 A-Lamp

Omni-Directional

LED	25,000 Hours average rated life, 120 Volts
------------	--

Applications


Ideal for outdoor applications where uniform omni-directional light output is required.

- + Outdoor Fixtures
- + Landscape Lights
- + Security Lights

Features	Benefits
Up to 85% less energy than halogen alternatives	Instant energy savings
Long life	Minimizes replacement and maintenance costs
UL wet location rated	Suitable for wet locations
Shatter resistant	Lower the risk of injury and breakage
ANSI construction compliant	Fits all A19 installations
Rated for totally enclosed fixtures	Can be used outdoors in totally enclosed fixtures
Works with photocells and motion sensors	Excellent for use with almost all outdoor control fixtures



Wet Location A19 A-Lamp



Specifications

Input Line Voltage:	120 VAC
Input Power	See Chart
Input Line Frequency	50/60HZ
Lamp Life (Rated)	25,000 hrs
Minimum Starting Temp	-30°C
Maximum Operating Temp	40°C
CRI	80

Warranties and Certifications:	Item #	Description	Voltage	Wattage	Incandescent Wattage Comparison	Lumens	LPW	CCT	CRI	R9	M.O.L. (inches)	Diameter (inches)
5 YEAR WARRANTY 	9.5W Wet Location A19 Omni-Directional A-Lamp – DIMMABLE											
	LED10A19DOD27KW	9.5W Wet Location Omni-Directional A-Lamp	120	9.5	60	800	84.2	2700K	80	>0	4.6	2.4
	LED10A19DOD30KW	9.5W Wet Location Omni-Directional A-Lamp	120	9.5	60	825	86.8	3000K	80	>0	4.6	2.4
	LED10A19DOD41KW	9.5W Wet Location Omni-Directional A-Lamp	120	9.5	60	850	89.5	4100K	80	>0	4.6	2.4
	LED10A19DOD50KW	9.5W Wet Location Omni-Directional A-Lamp	120	9.5	60	850	89.5	5000K	80	>0	4.6	2.4

*Based on 12 hours use per day

For the most up-to-date specs, please visit www.tcpi.com

