

	PRODUCT	FEATURES & BENEFITS	APPLICATIONS	OPTIONS
LED TROFFERS	<b>LED E-Series</b> 	<b>Recessed troffer has the appearance of fluorescent technology with a tube-line glow</b> <ul style="list-style-type: none"> <li>Long life: 50,000 hours</li> <li>Smooth, uniform dimming</li> <li>High efficiency alternative to T5, T8 &amp; T12 linear fluorescent troffers</li> <li>Excellent color consistency (CRI 82) &amp; superior lumen maintenance</li> </ul>	Grid Ceilings <ul style="list-style-type: none"> <li>Offices</li> <li>Restaurants</li> <li>Retail Stores</li> <li>Schools</li> <li>Hospitals</li> </ul>	<ul style="list-style-type: none"> <li><b>2'x2'</b> - 2,000L (25W), 4,000L (45W) &amp; <b>2'x4'</b> - 4,000L (45W), 6,800L (80W)</li> <li>3000K, 3500K, 4100K &amp; 5000K CCT</li> <li>120-277V Universal</li> <li>0-10V Dimming &amp; 120V Line Dimming</li> <li>Frosted White Lens &amp; Prismatic Lens</li> <li>Emergency Backup &amp; Chicago Plenum</li> </ul>
	<b>LED Premier Series</b> 	<b>Recessed troffer has full body, full panel diffusion with a soft warm glow appearance</b> <ul style="list-style-type: none"> <li>Long life: 50,000 hours</li> <li>Smooth, uniform dimming</li> <li>High efficiency alternative to T5, T8 &amp; T12 linear fluorescent troffers</li> <li>Excellent color consistency (CRI 82) &amp; superior lumen maintenance</li> </ul>	Grid Ceilings <ul style="list-style-type: none"> <li>Offices</li> <li>Restaurants</li> <li>Retail Stores</li> <li>Schools</li> <li>Hospitals</li> </ul>	<ul style="list-style-type: none"> <li><b>2'x2'</b> - 3,200L (35W), 4,200L (45W) &amp; <b>2'x4'</b> - 4,200L (45W), 6,800L (70W), 8,000L (89W)</li> <li>3000K, 3500K, 4100K &amp; 5000K CCT</li> <li>120-277V Universal</li> <li>0-10V Dimming &amp; 120V Line Dimming</li> <li>Frosted White Lens &amp; Prismatic Lens</li> <li>Emergency Backup &amp; Chicago Plenum</li> </ul>
	<b>LED Designer Series</b> 	<b>Volumetric luminaire for when appearance is most important</b> <ul style="list-style-type: none"> <li>Long life: 50,000 hours</li> <li>Smooth, uniform dimming</li> <li>High efficiency alternative to T5, T8 &amp; T12 linear fluorescent troffers</li> <li>Excellent color consistency (CRI 82) &amp; superior lumen maintenance</li> </ul>	Grid Ceilings <ul style="list-style-type: none"> <li>Offices</li> <li>Restaurants</li> <li>Retail Stores</li> <li>Schools</li> <li>Hospitals</li> </ul>	<ul style="list-style-type: none"> <li><b>2'x2'</b> - 2,200L (22.5W), 3,500L (35W), 4,400L (45W) &amp; <b>2'x4'</b> - 4,400L (45W), 7,000L (72W), 8,600L (97W)</li> <li>3000K, 3500K, 4100K &amp; 5000K CCT</li> <li>120-277V Universal</li> <li>0-10V Dimming &amp; 120V Line Dimming</li> <li>Volumetric Lens</li> <li>Emergency Backup &amp; Chicago Plenum</li> </ul>
LED LOW BAY	<b>LED Low Bay</b> 	<b>Ideal for mounting heights from 10 ft to 25 ft</b> <ul style="list-style-type: none"> <li>Long life: 50,000 hours</li> <li>Instant on</li> <li>High efficiency alternative to traditional metal halide &amp; linear fluorescent low bay systems</li> <li>Excellent color rendering (CRI 83)</li> <li>Heavy-duty 20 gauge housing constructed with code grade steel</li> </ul>	Ideal for mounting heights from 10 feet to 25 feet <ul style="list-style-type: none"> <li>Warehouses</li> <li>Commercial Facilities</li> <li>Manufacturing Facilities</li> <li>Aisles (Open and Stack)</li> </ul>	<ul style="list-style-type: none"> <li><b>4'</b> - 8,000L (85W)</li> <li>4100K &amp; 5000K CCT</li> <li>120-277V Universal, 347V &amp; 480V</li> <li>0-10V Dimming</li> <li>Prismatic Wraparound Lens, Prismatic Insert Lens &amp; Wire Guard</li> <li>Occupancy Sensors</li> <li>Hanging Kits</li> </ul>
	<b>LED High Bay</b> 	<b>Ideal for mounting heights up to 40 ft</b> <ul style="list-style-type: none"> <li>Long life: 50,000 hours</li> <li>Instant on</li> <li>High efficiency alternative to traditional metal halide &amp; linear fluorescent high bay systems</li> <li>Excellent color rendering (CRI 83)</li> <li>Heavy-duty 20 gauge housing constructed with code grade steel</li> </ul>	Ideal for mounting heights up to 40 feet <ul style="list-style-type: none"> <li>Warehouses</li> <li>Commercial Facilities</li> <li>Manufacturing Facilities</li> <li>Aisles (Open and Stack)</li> </ul>	<ul style="list-style-type: none"> <li><b>4'</b> - 12,000L (130W)</li> <li>4100K &amp; 5000K CCT</li> <li>120-277V Universal, 347V &amp; 480V</li> <li>0-10V Dimming</li> <li>Prismatic Wraparound Lens, Prismatic Insert Lens &amp; Wire Guard</li> <li>Occupancy Sensors</li> <li>Hanging Kits</li> </ul>
LED SKY BAY™	<b>LED Sky Bay™</b> 	<b>Ideal for mounting heights up to 60 ft</b> <ul style="list-style-type: none"> <li>Long life: 50,000 hours</li> <li>Instant on</li> <li>High efficiency alternative to traditional metal halide &amp; linear fluorescent high bay systems</li> <li>Excellent color rendering (CRI 83)</li> <li>Heavy-duty 20 gauge housing constructed with code grade steel</li> </ul>	Ideal for mounting heights up to 60 feet <ul style="list-style-type: none"> <li>Warehouses</li> <li>Commercial Facilities</li> <li>Manufacturing Facilities</li> <li>Aisles (Open and Stack)</li> </ul>	<ul style="list-style-type: none"> <li><b>4'</b> - 20,000L (210W), 24,000L (250W)</li> <li>4100K &amp; 5000K CCT</li> <li>120-277V Universal, 347V &amp; 480V</li> <li>0-10V Dimming</li> <li>Prismatic Wraparound Lens &amp; Wire Guard</li> <li>Occupancy Sensors</li> <li>Hanging Kits</li> </ul>

Actual performance may vary based on options selected and end user application.