



# LED A-Lamps

100w Equivalent • Omni-Directional

High efficiency A-Lamps. Light output in all directions to suit many applications.

## Limitless options for the following applications:

- General Lighting
- Floor Lamps
- Ceiling Fixtures
- Table Lamps
- Sconces

## Great features and benefits:

- Energy efficient: up to 85% more efficient than incandescent alternatives
- Smooth, uniform dimming when applicable
- Long life: 10,000/15,000/25,000 hour options
- Similar look and feel as incandescent alternative
- Excellent color consistency
- Available in 2700K, 3000K, 4100K and 5000K
- Fits any installations where a standard A-lamp is used

## Choices to meet your markets:

- 10,000 hour contractor series
- 15,000 hour high value series
- 25,000 hour elite series



L16A19N10  
L16A19N15  
L15A19D25



LED15A21D



we know light.™



### Applications:

Ideal for applications where uniform multi-directional light output is required.


- ✦ Table Lamps    ✦ Sconces    ✦ Decorative Fixtures
- ✦ Floor Lamps    ✦ Ceiling Fixtures
- ✦ Any general service lighting application

### Features

### Benefits

Up to 85% less energy than halogen alternatives	Instant energy savings
Long life	Minimizes replacement and maintenance costs
Very low heat generation	Perfect for sensitive display lighting such as art galleries
Excellent color consistency and CRI	Enhances colors of focal point while maintaining uniformity throughout lighting installation from lamp to lamp
UL approved for damp location	Can be used outdoors when protected from elements — withstands humidity indoors/outdoors
Shatter resistant	Lower the risk of injury and breakage
ANSI construction compliant	Fits all A-lamp installations

Dims to ≤ 5% of full light level when applicable



### Specifications

Input Line Voltage:	120 VAC
Input Line Frequency:	50/60HZ
Lamp Life (Rated):	10/15/25k hour options
Minimum Starting Temp:	-30°C
Maximum Operating Temp:	40°C
CRI:	80

Vapor tight or jelly jar applications may reduce life

Warranty	Item #	Description	Case Pack	Rated Life (hrs)	Wattage	Incandescent Wattage Comparison	Lumens	LPW	CCT	CRI	M.O.L. (inches)	Diameter (inches)	Enclosed/ Recessed Luminaire	EStar Rated	
<b>Non-Dimmable</b>															
<b>1</b> YEAR WARRANTY	L16A19N1027K4	LED 16W A19 ND 2700K 4PK	12	10,000	16	100	1500	93.8	2700K	80	4.6	2.5	Y		
	L16A19N1041K4	LED 16W A19 ND 4100K 4PK	12	10,000	16	100	1550	96.9	4100K	80	4.6	2.5	Y		
<b>3</b> YEAR WARRANTY	L16A19N1527K	LED 16W A19 ND 2700K	12	15,000	16	100	1600	100.0	2700K	80	4.6	2.5	Y	*	
	L16A19N1530K	LED 16W A19 ND 3000K	12	15,000	16	100	1625	101.6	3000K	80	4.6	2.5	Y	*	
	L16A19N1541K	LED 16W A19 ND 4100K	12	15,000	16	100	1650	103.1	4100K	80	4.6	2.5	Y	*	
	L16A19N1550K	LED 16W A19 ND 5000K	12	15,000	16	100	1675	104.7	5000K	80	4.6	2.5	Y	*	
<b>Dimmable</b>															
<b>3</b> YEAR WARRANTY	LED15A21D27K	LED 15W A21 DIM 2700K	12	15,000	15	100	1600	106.7	2700K	80	5.2	2.7	N	*	
	LED15A21D30K	LED 15W A21 DIM 3000K	12	15,000	15	100	1625	108.3	3000K	80	5.2	2.7	N	*	
	LED15A21D41K	LED 15W A21 DIM 4000K	12	15,000	15	100	1650	110.0	4000K	80	5.2	2.7	N	*	
	LED15A21D50K	LED 15W A21 DIM 5000K	12	15,000	15	100	1650	110.0	5000K	80	5.2	2.7	N	*	
<b>5</b> YEAR WARRANTY	L15A19D2527K	LED 15W A19 DIM 2700K	12	25,000	15	100	1600	106.7	2700K	80	4.6	2.5	Y	*	
	L15A19D2530K	LED 15W A19 DIM 3000K	12	25,000	15	100	1625	108.3	3000K	80	4.6	2.5	Y	*	
	L15A19D2541K	LED 15W A19 DIM 4100K	12	25,000	15	100	1650	110.0	4100K	80	4.6	2.5	Y	*	
	L15A19D2550K	LED 15W A19 DIM 5000K	12	25,000	15	100	1675	111.7	5000K	80	4.6	2.5	Y	*	

For the most up-to-date specs, please visit [www.tcp.com](http://www.tcp.com)