



# ProLine LED Lamps

**15,000 HOURS • 3 YEAR WARRANTY**

For an affordable LED upgrade, switch to TCP's ProLine LED Lamps. ProLine LEDs are available in multiple options from A-Lamps, to BR30 and PAR38 lamps. See how you can maximize savings and minimize maintenance cost with ProLine LEDs.

## LIMITLESS OPTIONS FOR THE FOLLOWING APPLICATIONS

- Commercial
- Retail
- Healthcare
- Industrial
- Residential

## FEATURES

- Long life: 15,000 hours
- Very low heat generation
- UL approved for damp location\*
- Inexpensive
- ANSI Construction Compliant

## BENEFITS

- Minimizes replacement and maintenance costs
- Perfect for sensitive display lighting such as art galleries
- Can be used outdoors when protected from elements—withstands humidity indoors/outdoors
- Save on cost
- Fits most general appliances

\*PAR38 Lamp—suitable for wet locations

## SPECIFICATIONS

Color Temperatures .....	2700K, 3000K
Input Line Voltage .....	120 VAC
Input Line Frequency .....	50/60HZ
Lamp Life (Rated) .....	15,000 hours
Minimum Starting Temp .....	-22F/-30C
Maximum Operating Temp .....	40°C
CRI .....	80



**3 YEAR WARRANTY**  
\* Based on 12 hours use per day



**LED**  
we know light.™





# ProLine LED Lamps

**15,000 HOURS • 3 YEAR WARRANTY**

ITEM #	DESCRIPTION	VOLTAGE	WATTS	INCANDESCENT WATTS	LPW	LUMENS	COLOR	HOURS	CRI	MOL (inches)	DIA (inches)	BASE	WARRANTY YEARS
<b>LED A-LAMP 60W Equivalent</b>													
<b>9W A19 • Non-Dimmable • 15,000 Hour</b>													
L60A19N15V27K	LED 9W A19 ND 2700K ProLine	120V	9	60	88.9	800	2700K	15,000	80	4.3	2.4	E26	3
<b>9W A19 • Dimmable • 15,000 Hour</b>													
L60A19D15V27K	LED 9W A19 DIM 2700K ProLine	120V	9	60	88.9	800	2700K	15,000	80	4.3	2.4	E26	3
<b>LED A-LAMP 100W Equivalent</b>													
<b>15W A19 • Dimmable • 15,000 Hour</b>													
L100A19D15V27K	LED 15W A19 DIM 2700K ProLine	120V	15	100	100.0	1500	2700K	15,000	80	4.5	2.6	E26	3
<b>LED BR30 65W Equivalent</b>													
<b>9W BR30 • Dimmable • 15,000 Hour</b>													
L65BR30D15V27K	LED 9W BR30 DIM 2700K ProLine	120V	9	65	72.2	650	2700K	15,000	80	4.75	3.7	E26	3
<b>LED PAR38 90W Equivalent*</b>													
<b>13W PAR38 • Dimmable • 15,000 Hour</b>													
L90P38D15V30KFL	LED 13W P38 DIM 30KFL ProLine 40° Beam Angle	120V	13	90	84.6	1100	3000K	15,000	80	5.3	4.8	E26	3
<b>LED All Glass A19 60W Equivalent</b>													
<b>8W A19 • Non-Dimmable • 15,000 Hour</b>													
LFF60A19N1527K	LED 60W EQ GLASS A19 ND 27K	120	8	60	90.6	725	2700K	15,000	80	4.2	2.4	E26	3
LFF60A19N1550K	LED 60W EQ GLASS A19 ND 50K	120	8	60	90.6	725	5000K	15,000	80	4.2	2.4	E26	3
<b>8W A19 • Dimmable • 15,000 Hour</b>													
LFF60A19D1527K	LED 60W EQ GLASS A19 DIM 27K	120	8	60	90.6	725	2700K	15,000	80	4.2	2.4	E26	3
LFF60A19D1550K	LED 60W EQ GLASS A19 DIM 50K	120	8	60	90.6	725	5000K	15,000	80	4.2	2.4	E26	3
<b>LED Decorative 40W Equivalent</b>													
<b>4W Deco • Dimmable • 15,000 Hour</b>													
FG25D40V27W	LED 4W G25 DIM 27K FR ProLine	120	4	40	87.5	350	2700K	15,000	80	4.5	3.2	E26	3
FB11D40V27E12C	LED 4W B11 DIM 27K E12 CL ProLine	120	4	40	87.5	350	2700K	15,000	80	3.5	1.4	E12	3

\* PAR38 IS SUITABLE FOR WET LOCATIONS—when exposed to water use only with device base up.



**3 YEAR WARRANTY**  
\* Based on 12 hours use per day



For the most up-to-date specs, please visit [www.tcp.com](http://www.tcp.com)

TCP®

325 Campus Dr. | Aurora, Ohio 44202 | P: 800-324-1496 | [tcp.com](http://tcp.com)

©TCP OCT 2018/WF128308