



LED PAR Lamps

DIMMABLE • WET LOCATION • 25,000 HOURS

TCP's award winning PAR lamps combine traditional beauty with top-notch technology. With the wide variety of options available—you can be sure to find the PAR lamps to meet your needs.

LIMITLESS OPTIONS FOR THE FOLLOWING APPLICATIONS

- Track lights
- Display lights
- Outdoor fixtures that protect lamps from the elements
- Recessed downlights
- Flood and spotlighting

FEATURES

BENEFITS

Up to 85% less energy than halogen alternatives	Instant energy savings
Long life	Minimizes replacement and maintenance costs
Unique full face optics	Provides designer grade light quality with same look as halogen replacements
Very low heat generation	Perfect for sensitive display lighting such as art galleries
Excellent color consistency and CRI	Enhances colors of focal point while maintaining uniformity throughout lighting installation from lamp to lamp
Light weight	Track or downlight installations are not strained by excess weight
UL approved for wet location	Suitable for wet locations—when exposed to water use only with device base up
Smooth clean outside housing	Seamlessly blends into lighting applications
Durable plastic	Lowers the risk for injury or breakage

SPECIFICATIONS

Color Temperatures.....2400K, 2700K, 3000K, 3500K, 4100K, 5000K
 Wattage Replacements..... 50W, 60W, 75W, 90W, 120W, 150W
 Input Line Voltage 120 VAC
 Input Line Frequency..... 50/60HZ
 Lamp Life (Rated)25,000 hours
 Minimum Starting Temp-30C
 Maximum Operating Temp..... 45°C
 CRI.....80



5 YEAR WARRANTY
 * Based on 12 hours use per day



Approved for enclosed fixtures however completely sealed fixture applications (ex: in ground landscape fixtures) may reduce life.



LED
we know light.™





LED PAR Lamps

DIMMABLE • WET LOCATION • 25,000 HOURS

ITEM #	DESCRIPTION	WATTS	LUMENS	LPW	COLOR	CRI	MEASURED CBCP	BEAM ANGLE
--------	-------------	-------	--------	-----	-------	-----	---------------	------------

LED PAR20 50W Equivalent Options

7W PAR20 • Dimmable • 25,000 Hours • 3.5" (MOI) x 2.5" (DIA)



LED8P20D24KFL	LED 7W P20 DIM 24KFL	7	550	78.6	2400K	80	—	40°
LED8P20D24KNFL	LED 7W P20 DIM 24KNFL	7	550	78.6	2400K	80	—	25°
LED8P20D27KFL	LED 7W P20 DIM 27KFL	7	600	85.7	2700K	80	1208	40°
LED8P20D27KFLB	LED 7W P20 DIM 27KFL BLACK	7	600	85.7	2700K	80	1208	40°
LED8P20D27KNFL	LED 7W P20 DIM 27KNFL	7	600	85.7	2700K	80	2030	25°
LED8P20D27KNFLB	LED 7W P20 DIM 27KNFL BLACK	7	600	85.7	2700K	80	2030	25°
LED8P20D27KSP	LED 7W P20 DIM 27KSP	7	600	85.7	2700K	80	4898	15°
LED8P20D30KFL	LED 7W P20 DIM 30KFL	7	625	89.3	3000K	80	1187	40°
LED8P20D30KFLB	LED 7W P20 DIM 30KFL BLACK	7	625	89.3	3000K	80	1187	40°
LED8P20D30KNFL	LED 7W P20 DIM 30KNFL	7	625	89.3	3000K	80	2050	25°
LED8P20D30KNFLB	LED 7W P20 DIM 30KNFL BLACK	7	625	89.3	3000K	80	2050	25°
LED8P20D30KSP	LED 7W P20 DIM 30KSP	7	625	89.3	3000K	80	5391	15°
LED8P20D35KFL	LED 7W P20 DIM 35KFL	7	675	96.4	3500K	80	1722	40°
LED8P20D35KNFL	LED 7W P20 DIM 35KNFL	7	675	96.4	3500K	80	4807	25°
LED8P20D41KFL	LED 7W P20 DIM 41KFL	7	675	96.4	4100K	80	1383	40°
LED8P20D41KFLB	LED 7W P20 DIM 41KFL BLACK	7	675	96.4	4100K	80	1383	40°
LED8P20D41KNFL	LED 7W P20 DIM 41KNFL	7	675	96.4	4100K	80	2174	25°
LED8P20D41KNFLB	LED 7W P20 DIM 41KNFL BLACK	7	675	96.4	4100K	80	2174	25°
LED8P20D41KSP	LED 7W P20 DIM 41KSP	7	675	96.4	4100K	80	5411	15°
LED8P20D50KFL	LED 7W P20 DIM 50KFL	7	700	100	5000K	80	1330	40°
LED8P20D50KFLB	LED 7W P20 DIM 50KFL BLACK	7	700	100	5000K	80	1330	40°
LED8P20D50KNFL	LED 7W P20 DIM 50KNFL	7	700	100	5000K	80	2172	25°
LED8P20D50KSP	LED 7W P20 DIM 50SP	7	700	100	5000K	80	5599	15°

LED PAR30 60W Equivalent Options

10W PAR30 Short Neck • Dimmable • 25,000 Hours • 3.5" (MOI) x 3.8" (DIA) PHASING OUT



LED10P30SD27KFL	LED 10W P30 DIM 27KFL	10	720	72.0	2700K	80	1714	40°
LED10P30SD30KSP	LED 10W P30 DIM 30KSP	10	720	72.0	3000K	80	—	15°
LED10P30SD41KFL	LED 10W P30 DIM 41KFL	10	720	72.0	4100K	80	1847	40°

LED PAR30 75W Equivalent Options

10W PAR30 Short Neck • Dimmable • 25,000 Hours • 3.6" (MOI) x 3.8" (DIA)



LED12P30SD24KFL	LED 10W P30SN DIM 24KFL	10	800	80.0	2400K	80	1619	40°
LED12P30SD24KNFL	LED 10W P30SN DIM 24KNFL	10	800	80.0	2400K	80	—	25°
LED12P30SD24KSP	LED 10W P30SN DIM 24KSP	10	800	80.0	2400K	80	—	15°
LED12P30SD27KFL	LED 10W P30SN DIM 27KFL	10	850	85.0	2700K	80	1817	40°
LED12P30SD27KFLB	LED 10W P30SN DIM 27KFL BLACK	10	850	85.0	2700K	80	1817	40°
LED12P30SD27KNFL	LED 10W P30SN DIM 27KNFL	10	850	85.0	2700K	80	4025	25°
LED12P30SD27KNFLB	LED 10W P30SN DIM 27KNFL BLACK	10	850	85.0	2700K	80	4025	25°
LED12P30SD27KSP	LED 10W P30SN DIM 27KSP	10	850	85.0	2700K	80	8042	15°
LED12P30SD30KFL	LED 10W P30SN DIM 30KFL	10	850	85.0	3000K	80	1858	40°
LED12P30SD30KFLB	LED 10W P30SN DIM 30KFL BLACK	10	850	85.0	3000K	80	1858	40°
LED12P30SD30KNFL	LED 10W P30SN DIM 30KNFL	10	850	85.0	3000K	80	4968	25°
LED12P30SD30KNFLB	LED 10W P30SN DIM 30KNFL BLACK	10	850	85.0	3000K	80	4968	25°
LED12P30SD30KSP	LED 10W P30SN DIM 30KSP	10	850	85.0	3000K	80	8380	15°
LED12P30SD30KSPB	LED 10W P30SN DIM 30KSP BLACK	10	850	85.0	3000K	80	8380	15°
LED12P30SD35KFL	LED 10W P30SN DIM 35KFL	10	850	85.0	3500K	80	2232	40°
LED12P30SD35KFLB	LED 10W P30SN DIM 35KFL BLACK	10	850	85.0	3500K	80	2232	40°

NOTE: All items come in shipping cartons of 12.

continued next page

For the most up-to-date specs, please visit www.tcp.com

TCP®

325 Campus Dr. | Aurora, Ohio 44202 | P: 800-324-1496 | tcp.com



LED PAR Lamps

DIMMABLE • WET LOCATION • 25,000 HOURS

ITEM #	DESCRIPTION	WATTS	LUMENS	LPW	COLOR	CRI	MEASURED CBCP	BEAM ANGLE
--------	-------------	-------	--------	-----	-------	-----	---------------	------------

LED PAR30 75W Equivalent Options *continued*

10W PAR30 Short Neck • Dimmable • 25,000 Hours • 3.6" (MOI) x 3.8" (DIA)



LED12P30SD35KNFL	LED 10W P30SN DIM 35KNFL	10	850	85.0	3500K	80	4402	25°
LED12P30SD35KNFLB	LED 10W P30SN DIM 35KNFL BLACK	10	850	85.0	3500K	80	4402	25°
LED12P30SD35KSP	LED 10W P30SN DIM 35KSP	10	850	85.0	3500K	80	—	15°
LED12P30SD41KFL	LED 10W P30SN DIM 41KFL	10	850	85.0	4100K	80	2247	40°
LED12P30SD41KFLB	LED 10W P30SN DIM 41KFL BLACK	10	850	85.0	4100K	80	2247	40°
LED12P30SD41KNFL	LED 10W P30SN DIM 41KNFL	10	850	85.0	4100K	80	4895	25°
LED12P30SD41KSP	LED 10W P30SN DIM 41KSP	10	850	85.0	4100K	80	8710	15°
LED12P30SD50KFL	LED 10W P30SN DIM 50KFL	10	850	85.0	5000K	80	2454	40°
LED12P30SD50KNFL	LED 10W P30SN DIM 50KNFL	10	850	85.0	5000K	80	5260	25°
LED12P30SD50KSP	LED 10W P30SN DIM 50KSP	10	850	85.0	5000K	80	9292	15°

10.5W PAR30 • Dimmable • 25,000 Hours • 4.6" (MOI) x 3.8" (DIA)



LED12P30D24KFL	LED 10.5W P30 DIM 24KFL	10.5	800	76.2	2400K	80	—	40°
LED12P30D24KNFL	LED 10.5W P30 DIM 24KNFL	10.5	800	76.2	2400K	80	—	25°
LED12P30D24KSP	LED 10.5W P30 DIM 24KSP	10.5	800	76.2	2400K	80	—	15°
LED12P30D27KFL	LED 10.5W P30 DIM 27KFL	10.5	850	81.0	2700K	80	2202	40°
LED12P30D27KFLB	LED 10.5W P30 DIM 27KFL BLACK	10.5	850	81.0	2700K	80	2202	40°
LED12P30D27KNFL	LED 10.5W P30 DIM 27KNFL	10.5	850	81.0	2700K	80	5031	25°
LED12P30D27KNFLB	LED 10.5W P30 DIM 27KNFL BLACK	10.5	850	81.0	2700K	80	5031	25°
LED12P30D27KSP	LED 10.5W P30 DIM 27KSP	10.5	850	81.0	2700K	80	9193	15°
LED12P30D27KSPB	LED 10.5W P30 DIM 27KSP BLACK	10.5	850	81.0	2700K	80	9193	15°
LED12P30D30KFL	LED 10.5W P30 DIM 30KFL	10.5	850	81.0	3000K	80	2389	40°
LED12P30D30KFLB	LED 10.5W P30 DIM 30KFL BLACK	10.5	850	81.0	3000K	80	2389	40°
LED12P30D30KNFL	LED 10.5W P30 DIM 30KNFL	10.5	850	81.0	3000K	80	5528	25°
LED12P30D30KNFLB	LED 10.5W P30 DIM 30KNFL BLACK	10.5	850	81.0	3000K	80	5528	25°
LED12P30D30KSP	LED 10.5W P30 DIM 30KSP	10.5	850	81.0	3000K	80	9006	15°
LED12P30D30KSPB	LED 10.5W P30 DIM 30KSP BLACK	10.5	850	81.0	3000K	80	9006	15°
LED12P30D35KFL	LED 10.5W P30 DIM 35KFL	10.5	850	81.0	3500K	80	2362	40°
LED12P30D35KNFL	LED 10.5W P30 DIM 35KNFL	10.5	850	81.0	3500K	80	5029	25°
LED12P30D35KSP	LED 10.5W P30 DIM 35KSP	10.5	850	81.0	3500K	80	9735	15°
LED12P30D41KFL	LED 10.5W P30 DIM 41KFL	10.5	850	81.0	4100K	80	2561	40°
LED12P30D41KFLB	LED 10.5W P30 DIM 41KFL BLACK	10.5	850	81.0	4100K	80	2561	40°
LED12P30D41KNFL	LED 10.5W P30 DIM 41KNFL	10.5	850	81.0	4100K	80	5781	25°
LED12P30D41KNFLB	LED 10.5W P30 DIM 41KNFL BLACK	10.5	850	81.0	4100K	80	5781	25°
LED12P30D41KSP	LED 10.5W P30 DIM 41KSP	10.5	850	81.0	4100K	80	9491	15°
LED12P30D41KSPB	LED 10.5W P30 DIM 41KSP BLACK	10.5	850	81.0	4100K	80	9491	15°
LED12P30D50KFL	LED 10.5W P30 DIM 50KFL	10.5	850	81.0	5000K	80	2437	40°
LED12P30D50KFLB	LED 10.5W P30 DIM 50KFL BLACK	10.5	850	81.0	5000K	80	2437	40°
LED12P30D50KNFL	LED 10.5W P30 DIM 50KNFL	10.5	850	81.0	5000K	80	5575	25°
LED12P30D50KSP	LED 10.5W P30 DIM 50KSP	10.5	850	81.0	5000K	80	9647	15°

LED PAR30 75W Equivalent Options

13.5W PAR30 • Dimmable • 25,000 Hours • 4.6" (MOI) x 3.8" (DIA)

LED14P30D24KFL	LED 13.5W P30 DIM 24KFL	13.5	1000	74.1	2400K	80	—	40°
LED14P30D24KNFL	LED 13.5W P30 DIM 24KNFL	13.5	1000	74.1	2400K	80	—	25°
LED14P30D24KNFLB	LED 13.5W P30 DIM 24KNFL BLACK	13.5	1000	74.1	2400K	80	—	25°
LED14P30D24KSP	LED 13.5W P30 DIM 24KSP	13.5	1000	74.1	2400K	80	—	15°
LED14P30D27KFL	LED 13.5W P30 DIM 27KFL	13.5	1050	77.8	2700K	80	2693	40°
LED14P30D27KFLB	LED 13.5W P30 DIM 27KFL BLACK	13.5	1050	77.8	2700K	80	2693	40°

NOTE: All items come in shipping cartons of 12.

continued next page

For the most up-to-date specs, please visit www.tcpi.com

TCP®

325 Campus Dr. | Aurora, Ohio 44202 | P: 800-324-1496 | tcpi.com



LED PAR Lamps

DIMMABLE • WET LOCATION • 25,000 HOURS

ITEM #	DESCRIPTION	WATTS	LUMENS	LPW	COLOR	CRI	MEASURED CBCP	BEAM ANGLE
--------	-------------	-------	--------	-----	-------	-----	---------------	------------

LED PAR30 75W Equivalent Options *continued*

13.5W PAR30 • Dimmable • 25,000 Hours • 4.6" (MOI) x 3.8" (DIA)



LED14P30D27KNFL	LED 13.5W P30 DIM 27KNFL	13.5	1050	77.8	2700K	80	5808	25°
LED14P30D27KNFLB	LED 13.5W P30 DIM 27KNFL BLACK	13.5	1050	77.8	2700K	80	5808	25°
LED14P30D27KSP	LED 13.5W P30 DIM 27KSP	13.5	1050	77.8	2700K	80	10563	15°
LED14P30D27KSPB	LED 13.5W P30 DIM 27KSP BLACK	13.5	1050	77.8	2700K	80	10563	15°
LED14P30D30KFL	LED 13.5W P30 DIM 30KFL	13.5	1050	77.8	3000K	80	2849	40°
LED14P30D30KFLB	LED 13.5W P30 DIM 30KFLB	13.5	1050	77.8	3000K	80	2849	40°
LED14P30D30KNFL	LED 13.5W P30 DIM 30KNFL	13.5	1050	77.8	3000K	80	6392	25°
LED14P30D30KNFLB	LED 13.5W P30 DIM 30KNFL BLACK	13.5	1050	77.8	3000K	80	6392	25°
LED14P30D30KSP	LED 13.5W P30 DIM 30KSP	13.5	1050	77.8	3000K	80	11181	15°
LED14P30D30KSPB	LED 13.5W P30 DIM 30KSP BLACK	13.5	1050	77.8	3000K	80	11181	15°
LED14P30D35KFL	LED 13.5W P30 DIM 35KFL	13.5	1050	77.8	3500K	80	—	40°
LED14P30D35KFLB	LED 13.5W P30 DIM 35KFL BLACK	13.5	1050	77.8	3500K	80	—	40°
LED14P30D35KNFL	LED 13.5W P30 DIM 35KNFL	13.5	1050	77.8	3500K	80	—	25°
LED14P30D35KSP	LED 13.5W P30 DIM 35KSP	13.5	1050	77.8	3500K	80	—	15°
LED14P30D41KFL	LED 13.5W P30 DIM 41KFL	13.5	1050	77.8	4100K	80	2661	40°
LED14P30D41KFLB	LED 13.5W P30 DIM 41KFL BLACK	13.5	1050	77.8	4100K	80	2661	40°
LED14P30D41KNFL	LED 13.5W P30 DIM 41KNFL	13.5	1050	77.8	4100K	80	5781	25°
LED14P30D41KNFLB	LED 13.5W P30 DIM 41KNFL BLACK	13.5	1050	77.8	4100K	80	5781	25°
LED14P30D41KSP	LED 13.5W P30 DIM 41KSP	13.5	1050	77.8	4100K	80	12465	15°
LED14P30D41KSPB	LED 13.5W P30 DIM 41KSP BLACK	13.5	1050	77.8	4100K	80	12465	15°
LED14P30D50KFL	LED 13.5W P30 DIM 50KFL	13.5	1050	77.8	5000K	80	2837	40°
LED14P30D50KFLB	LED 13.5W P30 DIM 50KFL BLACK	13.5	1050	77.8	5000K	80	2837	40°
LED14P30D50KNFL	LED 13.5W P30 DIM 50KNFL	13.5	1050	77.8	5000K	80	5875	25°
LED14P30D50KSP	LED 13.5W P30 DIM 50KSP	13.5	1050	77.8	5000K	80	12073	15°

LED PAR38 90W Equivalent Options

13.5W PAR38 • Dimmable • 25,000 Hours • 5.3" (MOI) x 4.8" (DIA)



LED14P38D24KFL	LED 13.5W P38 DIM 24KFL	13.5	1000	74.1	2400K	80	—	40°
LED14P38D24KNFL	LED 13.5W P38 DIM 24KNFL	13.5	1000	74.1	2400K	80	—	25°
LED14P38D24KSP	LED 13.5W P38 DIM 24KSP	13.5	1000	74.1	2400K	80	—	15°
LED14P38D27KFL	LED 13.5W P38 DIM 27KFL	13.5	1050	77.8	2700K	80	2480	40°
LED14P38D27KNFL	LED 13.5W P38 DIM 27KNFL	13.5	1050	77.8	2700K	80	7649	25°
LED14P38D27KNFLB	LED 13.5W P38 DIM 27KNFL BLACK	13.5	1050	77.8	2700K	80	7649	25°
LED14P38D27KSP	LED 13.5W P38 DIM 27KSP	13.5	1050	77.8	2700K	80	12073	15°
LED14P38D27KSPB	LED 13.5W P38 DIM 27KSP BLACK	13.5	1050	77.8	2700K	80	12073	15°
LED14P38D30KFL	LED 13.5W P38 DIM 30KFL	13.5	1050	77.8	3000K	80	2498	40°
LED14P38D30KNFL	LED 13.5W P38 DIM 30KNFL	13.5	1050	77.8	3000K	80	7606	25°
LED14P38D30KSP	LED 13.5W P38 DIM 30KSP	13.5	1050	77.8	3000K	80	11845	15°
LED14P38D30KWFL	LED 13.5W P38 DIM 30KWFL	13.5	1050	77.8	3000K	80	—	60°
LED14P38D35KFL	LED 13.5W P38 DIM 35KFL	13.5	1050	77.8	3500K	80	2736	40°
LED14P38D35KFLB	LED 13.5W P38 DIM 35KFL BLACK	13.5	1050	77.8	3500K	80	2736	40°
LED14P38D35KNFL	LED 13.5W P38 DIM 35KNFL	13.5	1050	77.8	3500K	80	—	25°
LED14P38D35KSP	LED 13.5W P38 DIM 35KSP	13.5	1050	77.8	3500K	80	12856	15°
LED14P38D41KFL	LED 13.5W P38 DIM 41KFL	13.5	1050	77.8	4100K	80	2678	40°
LED14P38D41KFLB	LED 13.5W P38 DIM 41KFL BLACK	13.5	1050	77.8	4100K	80	2678	40°
LED14P38D41KNFL	LED 13.5W P38 DIM 41KNFL	13.5	1050	77.8	4100K	80	8310	25°
LED14P38D41KSP	LED 13.5W P38 DIM 41KSP	13.5	1050	77.8	4100K	80	13535	15°
LED14P38D41KSPB	LED 13.5W P38 DIM 41KSP BLACK	13.5	1050	77.8	4100K	80	13535	15°
LED14P38D50KFL	LED 13.5W P38 DIM 50KFL	13.5	1050	77.8	5000K	80	2647	40°

NOTE: All items come in shipping cartons of 12.

continued next page

For the most up-to-date specs, please visit www.tcpi.com



LED PAR Lamps

DIMMABLE • WET LOCATION • 25,000 HOURS

ITEM #	DESCRIPTION	WATTS	LUMENS	LPW	COLOR	CRI	MEASURED CBCP	BEAM ANGLE
--------	-------------	-------	--------	-----	-------	-----	---------------	------------

LED PAR38 90W Equivalent Options *continued*

13.5W PAR38 • Dimmable • 25,000 Hours • 5.3" (MOI) x 4.8" (DIA)

LED14P38D50KFLB	LED 13.5W P38 DIM 50KFL BLACK	13.5	1050	77.8	5000K	80	2647	40°
LED14P38D50KNFL	LED 13.5W P38 DIM 50KNFL	13.5	1050	77.8	5000K	80	8071	25°
LED14P38D50KSP	LED 13.5W P38 DIM 50KSP	13.5	1050	77.8	5000K	80	12418	15°

LED PAR38 120W Equivalent Options

15W PAR38 • Dimmable • 25,000 Hours • 5.3" (MOI) x 4.8" (DIA)



LED17P38D24KFL	LED 15W P38 DIM 24KFL	15	1050	70.0	2400K	80	—	40°
LED17P38D24KNFL	LED 15W P38 DIM 24KNFL	15	1050	70.0	2400K	80	—	25°
LED17P38D24KSP	LED 15W P38 DIM 24KSP	15	1050	70.0	2400K	80	—	15°
LED17P38D27KFL	LED 15W P38 DIM 27KFL	15	1200	80.0	2700K	80	2757	40°
LED17P38D27KFLB	LED 15W P38 DIM 27KFL BLACK	15	1200	80.0	2700K	80	2757	40°
LED17P38D27KNFL	LED 15W P38 DIM 27KNFL	15	1200	80.0	2700K	80	8857	25°
LED17P38D27KSP	LED 15W P38 DIM 27KSP	15	1200	80.0	2700K	80	16239	15°
LED17P38D30KFL	LED 15W P38 DIM 30KFL	15	1200	80.0	3000K	80	3106	40°
LED17P38D30KFLB	LED 15W P38 DIM 30KFL BLACK	15	1200	80.0	3000K	80	3106	40°
LED17P38D30KNFL	LED 15W P38 DIM 30KNFL	15	1200	80.0	3000K	80	9274	25°
LED17P38D30KNFLB	LED 15W P38 DIM 30KNFL BLACK	15	1200	80.0	3000K	80	9274	25°
LED17P38D30KSP	LED 15W P38 DIM 30KSP	15	1200	80.0	3000K	80	18492	15°
LED17P38D30KSPB	LED 15W P38 DIM 30KSP BLACK	15	1200	80.0	3000K	80	18492	15°
LED17P38D30KWFLB	LED 15W P38 DIM 30KWFL BLACK	15	1200	80.0	3000K	80	—	60°
LED17P38D35KFL	LED 15W P38 DIM 35KFL	15	1200	80.0	3500K	80	2994	40°
LED17P38D35KFLB	LED 15W P38 DIM 35KFL BLACK	15	1200	80.0	3500K	80	2994	40°
LED17P38D35KNFL	LED 15W P38 DIM 35KNFL	15	1200	80.0	3500K	80	9405	25°
LED17P38D35KNFLB	LED 15W P38 DIM 35KNFL BLACK	15	1200	80.0	3500K	80	9405	25°
LED17P38D35KSP	LED 15W P38 DIM 35KSP	15	1200	80.0	3500K	80	18094	15°
LED17P38D41KFL	LED 15W P38 DIM 41KFL	15	1200	80.0	4100K	80	2870	40°
LED17P38D41KFLB	LED 15W P38 DIM 41KFL BLACK	15	1200	80.0	4100K	80	2870	40°
LED17P38D41KNFL	LED 15W P38 DIM 41KNFL	15	1200	80.0	4100K	80	9288	25°
LED17P38D41KNFLB	LED 15W P38 DIM 41KNFL BLACK	15	1200	80.0	4100K	80	9288	25°
LED17P38D41KSP	LED 15W P38 DIM 41KSP	15	1200	80.0	4100K	80	18408	15°
LED17P38D41KSPB	LED 15W P38 DIM 41KSP BLACK	15	1200	80.0	4100K	80	18408	15°
LED17P38D50KFL	LED 15W P38 DIM 50KFL	15	1200	80.0	5000K	80	2713	40°
LED17P38D50KFLB	LED 15W P38 DIM 50KFL BLACK	15	1200	80.0	5000K	80	2713	40°
LED17P38D50KNFL	LED 15W P38 DIM 50KNFL	15	1200	80.0	5000K	80	9387	25°
LED17P38D50KSP	LED 15W P38 DIM 50KSP	15	1200	80.0	5000K	80	19721	15°

LED PAR38 HIGH OUTPUT 150W Equivalent Options

18.5W PAR38 High Output • Dimmable • 25,000 Hours • 5.3" (MOI) x 4.8" (DIA)

LED17HOP38D27KFL	LED 18.5W HOP38 DIM 27KFL	18.5	1800	97.3	2700K	80	4346	40°
LED17HOP38D27KNFL	LED 18.5W HOP38 DIM 27KNFL	18.5	1800	97.3	2700K	80	9299	25°
LED17HOP38D27KSP	LED 18.5W HOP38 DIM 27KSP	18.5	1800	97.3	2700K	80	21535	15°
LED17HOP38D27KSPB	LED 18.5W HOP38 DIM 27KSP BLACK	18.5	1800	97.3	2700K	80	21535	15°
LED17HOP38D30KFL	LED 18.5W HOP38 DIM 30KFL	18.5	1825	98.6	3000K	80	4365	40°
LED17HOP38D30KFLB	LED 18.5W HOP38 DIM 30KFL BLACK	18.5	1825	98.6	3000K	80	4365	40°
LED17HOP38D30KNFL	LED 18.5W HOP38 DIM 30KNFL	18.5	1825	98.6	3000K	80	12782	25°
LED17HOP38D30KNFLB	LED 18.5W HOP38 DIM 30KNFL BLACK	18.5	1825	98.6	3000K	80	12782	25°
LED17HOP38D30KSP	LED 18.5W HOP38 DIM 30KSP	18.5	1825	98.6	3000K	80	23699	15°
LED17HOP38D30KSPB	LED 18.5W HOP38 DIM 30KSP BLACK	18.5	1825	98.6	3000K	80	23699	15°

NOTE: All items come in shipping cartons of 12.

continued next page

For the most up-to-date specs, please visit www.tcp.com

TCP®

325 Campus Dr. | Aurora, Ohio 44202 | P: 800-324-1496 | tcp.com



LED PAR Lamps

DIMMABLE • WET LOCATION • 25,000 HOURS

ITEM #	DESCRIPTION	WATTS	LUMENS	LPW	COLOR	CRI	MEASURED CBCP	BEAM ANGLE
--------	-------------	-------	--------	-----	-------	-----	---------------	------------

LED PAR38 HIGH OUTPUT 150W Equivalent Options *continued*

18.5W PAR38 High Output • Dimmable • 25,000 Hours • 5.3" (MOI) x 4.8" (DIA)



LED17HOP38D35KFL	LED 18.5W HOP38 DIM 35KFL	18.5	1850	100.0	3500K	80	3481	40°
LED17HOP38D35KFLB	LED 18.5W HOP38 DIM 35KFL BLACK	18.5	1850	100.0	3500K	80	3481	40°
LED17HOP38D35KNFL	LED 18.5W HOP38 DIM 35KNFL	18.5	1850	100.0	3500K	80	11664	25°
LED17HOP38D35KSP	LED 18.5W HOP38 DIM 35KSP	18.5	1850	100.0	3500K	80	23145	15°
LED17HOP38D35KWFL	LED 18.5W HOP38 DIM 35KWFL	18.5	1850	100.0	3500K	80	—	60°
LED17HOP38D41KFL	LED 18.5W HOP38 DIM 41KFL	18.5	1900	102.7	4100K	80	4604	40°
LED17HOP38D41KNFL	LED 18.5W HOP38 DIM 41KNFL	18.5	1900	102.7	4100K	80	11614	25°
LED17HOP38D41KSP	LED 18.5W HOP38 DIM 41KSP	18.5	1900	102.7	4100K	80	22458	15°
LED17HOP38D50KFL	LED 18.5W HOP38 DIM 50KFL	18.5	2000	108.1	5000K	80	4446	40°
LED17HOP38D50KNFL	LED 18.5W HOP38 DIM 50KNFL	18.5	2000	108.1	5000K	80	12467	25°
LED17HOP38D50KSP	LED 18.5W HOP38 DIM 50KSP	18.5	2000	108.1	5000K	80	21535	15°

NOTE: All items come in shipping cartons of 12.

For the most up-to-date specs, please visit www.tcpi.com

TCP®

325 Campus Dr. | Aurora, Ohio 44202 | P: 800-324-1496 | tcpi.com

©TCP AUG 2019/WF164451