

Specifications:

Operating voltage 120-277Vac, 50/60Hz
 Input Voltage 120-230-277-347VAC
 Operational Frequencies 50/60 Hz
 Rated load 800VA @ 120VAC Ballast
 1200VA @ 277VAC Ballast
 Standby Power Consumption 120V – 130mW – .13W
 277V – 450mW – .45W
 Time Delay 30 seconds – 20 minutes
 (factory set to 30 sec –
 no power required to set)
 Detection zone Max.(D x H): 16m x 15m
 Mounting height 15m Max.
 Motion detection 0.5-3m/s
 Operating temperature..... -20°C - 60°C
 IP rating IP20
 Operating Temperature Range.... 14-160° F (-10-71° C)
 Cold Storage Operating
 Temperature Range -40-160° F (-40-71° C)
 Storage Temperature Range -14-160° F (-25-71° C)
 Relative Humidity 20-90% non-condensing
 Color White
 Warranty 5 year limited warranty



Listing

RoHS Compliant

Warranty

Five year limited warranty against defects in manufacturing

Ordering Matrix

Item #	DESCRIPTION
LS1Q	PIR Fixture Mount High Bay Sensor
LS1D	PIR Fixture Mount High Bay Sensor with Daylight Harvest and Bi-level Dimming Functionality

For the most up-to-date specs and warranty information, please visit www.tcpi.com

Specifications and dimensions subject to change without notice.

TECHNOLOGY CAST IN A BEAUTIFUL LIGHT

For over 20 years, TCP has been designing, developing and delivering energy-efficient lighting into the market. Thanks to our cutting-edge technology and manufacturing expertise, we have shipped billions of high quality lighting products. With TCP, you can count on a lighting product that is designed to meet the needs of the market - that transforms your surroundings and envelopes you in warmth - lighting that generates beauty with every flip of the switch.

Sales:

Date:

Model:

Project:

Rep:

Catalog Number:

Type:

Notes:



For more information on the quality and care TCP can deliver, call us at **800.324.1496** or visit tcpi.com

325 Campus Dr. | Aurora, Ohio 44202 | P: 800.324.1496 | F: 877.487.0516