



LED Beveled Face Color & Wattage Selectable Downlights

Product Specifications



For quick, easy, and affordable LED upgrades, switch to TCP's LED Downlights. TCP's Beveled Face Color & Wattage Selectable Downlights have both E26 and direct wire options, PMMA plastic to prevent lens discoloration, and quick-snap holding arms to quickly attach to a recessed can. With a traditional look, these downlights provide smooth, even light in the color temperature you need.

Reasons to choose the LED Beveled Face Color & Wattage Selectable Downlights from TCP

- Color selectable — choose between 2700K/3000K/3500K or 3000K/4000K/5000K
- Wattage selectable — choose between 8W, 10.5W and 14.5W
- Excellent color consistency and CRI enhances colors of the focal point while maintaining uniformity through-out the lighting installation
- Smooth, uniform dimming 100 - 10%
- Long, 50,000 hour life minimizes replacement and maintenance costs
- Very low heat generation makes the downlight perfect for sensitive display lighting
- Durable PMMA plastic housing resists discoloration
- Easy installation – mounts directly to a 6" recessed can and includes both E26 and direct wire power options
- Energy Star Certified

Ideal Applications

- Commercial
- Industrial
- Retail
- Residential
- Healthcare

Specifications

Color Temperatures 2700K/3000K/3500K or 3000K/4000K/5000K
 Wattage options 8W, 10.5W, 14.5W
 Input Line Voltage 120 VAC
 Input Line Frequency 50/60HZ
 Lamp Life (Rated) 50,000 hours

Minimum Starting Temp -22°F/-30°C
 Maximum Operating Temp 104°F/40°C
 CRI 80
 IC-rated for direct contact with insulation
 UL approved for damp location (indoor only)—outdoor environment may cause yellowing of the white trim. This is not covered by warranty.



Specifications



6 inch Dimmable Downlight

| ITEM # | DESCRIPTION | VOLTAGE | WATTS | INCANDES. WATTS | LPW | LUMENS | COLOR | MOL CRI | DIA (inches) | BEAM ANGLE | BASE | ENERGY STAR | WARRANTY YEARS | |
|--|--|---------|-------------|-----------------|---|--|-------------------|---------|--------------|------------|------|-------------|----------------|---|
| LED 120W Equivalent Options | | | | | | | | | | | | | | |
| DR56 Downlight • Dimmable • 50,000 Hour | | | | | | | | | | | | | | |
| L120DR56DCCT1 | 5"/6" LED Beveled Face Color & Wattage Selectable Downlight 2700K/3000K/3500K | 120V | 8/10.5/14.5 | 120 | 8W: 95.6/106.3/106.3 10.5W: 95.2/104.8/104.8 14.5W: 86.9/96.6/96.6 | 8W: 765/850/850 10.5W: 1000/1100/1100 14.5W: 1260/1400/1400 | 2700K/3000K/3500K | 80 | 3.0 | 7.4 | 120° | E26 | ★ | 5 |
| L120DR56DCCT2 | 5"/6" LED Beveled Face Color & Wattage Selectable Downlight 3000K/4000K/5000K | 120V | 8/10.5/14.5 | 120 | 8W: 113.8/118.1/115 10.5W: 104.8/110.5/106.7 14.5W: 100/95.5/102.3 | 8W: 910/945/920 10.5W: 1100/1160/1120 14.5W: 1450/1470/1490 | 3000K/4000K/5000K | 80 | 3.0 | 7.4 | 120° | E26 | ★ | 5 |