



# LED High Lumen PAR38 Lamps

## Product Specifications



TCP's LED High Lumen PAR38 lamps combine traditional beauty with top-notch technology for wherever bright light is needed.

### Reasons to choose the LED High Lumen PAR Lamps from TCP

- Up to 85% more efficient than halogen
- Provides instant energy savings
- Long 25,000 hour rated life minimizes replacement and maintenance costs
- Wet location rated for outdoor use
- Available in Flood and Narrow Flood beam angles for every application
- 95 CRI rating and high R9 value enhance surrounding colors
- Works on 120 - 277V
- Smooth Heat Sink construction seamlessly blends into lighting applications

### Ideal Applications

- Large Outdoor Spaces
- Security
- Barns
- Garages
- Parking Structures
- Large Indoor Spaces

### Specifications:

Color Temperatures ..... 2700K, 3000K, 3500K,  
4100K, 5000K  
 Input Line Voltage ..... 120-277V  
 Input Line Frequency ..... 50/60HZ  
 Lamp Life (Rated) ..... 25,000 hours

Beam Angle ..... 25° Narrow Flood, 40° Flood  
 CRI ..... 95

Wet location rated for outdoor use.  
 Not recommended for use in enclosed fixtures.





# LED High Lumen PAR38 Lamps

## Specifications:



ITEM #	DESCRIPTION	LED WATTS	WATTAGE EQUIVALENT	LUMENS	LPW	CRI	R9	COLOR TEMP	BULB COLOR	BEAM ANGLE	BASE
<b>P38 28W 40° Flood • Non Dimmable • 25,000 hours</b>											
L28P38N25UNV27KFL	LED 28W P38 ND UNV 27K FL	28	250	3000	107.14	95	60	2700K	SOFT WHITE	40°	E26
L28P38N25UNV30KFL	LED 28W P38 ND UNV 30K FL	28	250	3100	110.71	95	60	3000K	WARM WHITE	40°	E26
L28P38N25UNV35KFL	LED 28W P38 ND UNV 35K FL	28	250	3100	110.71	95	60	3500K	BRIGHT WHITE	40°	E26
L28P38N25UNV41KFL	LED 28W P38 ND UNV 41K FL	28	250	3100	110.71	95	60	4100K	COOL WHITE	40°	E26
L28P38N25UNV50KFL	LED 28W P38 ND UNV 50K FL	28	250	3100	110.71	95	60	5000K	DAYLIGHT	40°	E26
<b>P38 28W 25° Narrow Flood • Non Dimmable • 25,000 hours</b>											
L28P38N25UNV27KNFL	LED 28W P38 ND UNV 27K NFL	28	250	3000	107.14	95	60	2700K	SOFT WHITE	25°	E26
L28P38N25UNV30KNFL	LED 28W P38 ND UNV 30K NFL	28	250	3100	110.71	95	60	3000K	WARM WHITE	25°	E26
L28P38N25UNV35KNFL	LED 28W P38 ND UNV 35K NFL	28	250	3100	110.71	95	60	3500K	BRIGHT WHITE	25°	E26
L28P38N25UNV41KNFL	LED 28W P38 ND UNV 41K NFL	28	250	3100	110.71	95	60	4100K	COOL WHITE	25°	E26
L28P38N25UNV50KNFL	LED 28W P38 ND UNV 50K NFL	28	250	3100	110.71	95	60	5000K	DAYLIGHT	25°	E26

