



LED Round Luminaire

Pendant or Surface Mount

Product Specifications



TCP's LED Round Luminaire features a slim, low-profile design with full-panel diffusion and superior uniformity. This designer-grade fixture provides exceptional light output for both surface and pendant mount applications. It offers a cost-effective solution to maximize savings and take advantage of utility rebates without sacrificing performance.

Reasons to choose the LED Round Luminaire from TCP

- Uses up to 51% less energy than fluorescent alternatives
- Long 50,000 hour rated life
- Excellent color consistency & CRI
- Mercury free
- Option for Pendant or Surface Mount Installation
- Utilizes edge-lit technology
- Slim, low-profile design
- Pendant mount can be adjusted to hang between 12" – 54" from ceiling

Ideal Applications

- Offices
- Retail Stores
- Schools
- Hospitality
- Restaurants
- Healthcare

Specifications:

Input Line Voltage 120-277 VAC
 Input Line Frequency..... 50/60Hz
 Wattage..... 36W
 Lumens 3600L
 Lumens per Watt 100LPW
 Rated Life..... 50,000 Hours
 Minimum Starting Temperature-20°C

Maximum Operating Temperature..... 40°C
 CRI..... >80
 Power Factor>90%
 THD.....<20%
 Ratings UL/cUL damp location rated
 Controls..... 0-10V dimming

Applications

TCP LED Round Luminaires are cost-effective, high-efficiency alternatives to traditional fluorescent luminaires. Featuring a slim, low-profile design, our LED Round Luminaires use edge-lit technology to deliver full-panel diffusion and superior uniformity. Applications include offices, schools, retail locations, healthcare, hospitality and other commercial ceilings.

Construction

- Housing: suspension-mounted light engine with remote driver and wiring compartment
- Frame: aluminum
- Lens: integrated diffuser
- Two-piece pendant hanger allows for easy installation
- Pendant mount can be adjusted to hang 12"-54" from ceiling


Electrical

- UL/cUL damp location rated
- 0-10V dimming driver (standard)
- System rated for long 50,000 hour life

Optics

- Innovative edge-lit technology paired with acrylic light guide and thin, frosted, white diffuser
- 120° beam angle
- Delivers full-panel diffusion and excellent uniformity

Item Number	
Notes	Type



Listings

UL/cUL Listed
RoHS Compliant

Warranty

Five year limited warranty against defects in manufacturing.

Catalog Ordering Matrix Example: RPD24UZD3641K

Item #	Description	Lumens	LPW	Power Factor	CCT	CRI	Life (Hours)	Dia. (in.)
RPD24UZD3630K	RND PENDANT 3600L 010 DIM 30K	3600	100	>0.9	3000K	80	50,000	24
RPD24UZD3641K	RND PENDANT 3600L 010 DIM 41K	3600	100	>0.9	4100K	80	50,000	24
RPD24UZD3650K	RND PENDANT 3600L 010 DIM 50K	3600	100	>0.9	5000K	80	50,000	24

Accessories

Item #	Description
RPDSURFMNTJBOX	Junction Box required for surface mount application



For the most up-to-date specs and warranty information, please visit www.tcp.com