



# Pro Line Family of LED Lamps

## Product Specifications



For an affordable LED upgrade, switch to TCP's Pro Line LED Lamps. Pro Line LEDs are available in multiple options from A-Lamps, to BR30 and PAR38 lamps. See how you can maximize savings and minimize maintenance costs with Pro Line LED Lamps.

### Reasons to choose the Pro Line from TCP

- Long life: 15,000 hours minimizes replacement and maintenance costs
- Inexpensive alternative for cost-sensitive projects
- ANSI Construction Compliant to fit most general applications
- UL approved for damp location means lamps can be used outdoors when protected from the elements. (All PAR lamps are suitable for wet locations.)

### Ideal Applications

- Commercial
- Retail
- Industrial
- Residential

### Specifications

Input Line Voltage .....	120 VAC	CRI .....	80
Input Line Frequency .....	50/60HZ	Warranty .....	3 Years
Lamp Life (Rated) .....	15,000 hours	* All A-Lamps, Deco, and R/BR Floods are approved for use in Enclosed Luminaires	
Minimum Starting Temp .....	-22°F/-30°C	* PARs are not recommended for use in Enclosed Luminaires	
Maximum Operating Temp .....	104°F/40°C		



## Specifications



A-Lamps  
60W/100W equivalent



BR30  
65W equivalent



PAR38  
90W equivalent



All Glass A-Lamp  
60W equivalent



G25  
40W equivalent

ITEM #	DESCRIPTION	WATTS	INCAND. WATTS	CRI	LUMENS	LPW	COLOR	FINISH	HOURS	MOL (inches)	DIA (inches)	BASE	WARRANTY YEARS
<b>LED All Glass A-LAMP • 15,000 Hour</b>													
<b>4.5W A19 • Dimmable</b>													
LFF40A19D1527K	LED 40W EQ GLASS A19 DIM 27K FR	4.5	40	80	425	94.4	2700K	FROST	15,000	4.2	2.4	E26	3
LFC40A19D1527K	LED 40W EQ GLASS A19 DIM 27K CL	4.5	40	80	425	94.4	2700K	CLEAR	15,000	4.2	2.4	E26	3
<b>5W A19 • Non-Dimmable</b>													
LFF40A19N1527K	LED 40W EQ GLASS A19 ND 27K FR	5	40	80	425	85.0	2700K	Frosted	15,000	4.2	2.4	E26	3
LFF40A19N1550K	LED 40W EQ GLASS A19 ND 50K FR	5	40	80	425	85.0	5000K	Frosted	15,000	4.2	2.4	E26	3
LFC40A19N1527K	LED 40W EQ GLASS A19 ND 27K CL	5	40	80	425	85.0	2700K	Clear	15,000	4.2	2.4	E26	3
LFC40A19N1550K	LED 40W EQ GLASS A19 ND 50K CL	5	40	80	425	85.0	5000K	Clear	15,000	4.2	2.4	E26	3
<b>8W A19 • Dimmable</b>													
LFF60A19D1550K	LED 60W EQ GLASS A19 DIM 50K	8	60	80	725	90.6	5000K	Frosted	15,000	4.2	2.4	E26	3
<b>8W A19 • Non-Dimmable</b>													
LFC60A19N1527K	LED 60W EQ GLASS A19 ND 27K CL	8	60	80	725	90.6	2700K	Clear	15,000	4.2	2.4	E26	3
LFC60A19N1550K	LED 60W EQ GLASS A19 ND 50K CL	8	60	80	725	90.6	5000K	Clear	15,000	4.2	2.4	E26	3
<b>LED All Glass Decorative 40W Equivalent • Dimmable • 15,000 Hour</b>													
FG25D40V27W	LED 4W G25 DIM 27K FR Pro	4	40	80	350	87.5	2700K	Frosted	15,000	4.5	3.2	E26	3
<b>LED A-LAMP • 15,000 Hour</b>													
<b>9W A19 • Non-Dimmable</b>													
L60A19N15V27K	LED 9W A19 ND 2700K Pro Line	9	60	80	800	88.9	2700K	Frosted	15,000	4.3	2.4	E26	3
<b>15W A19 • Dimmable</b>													
L100A19D15V27K	LED 15W A19 DIM 2700K Pro Line	15	100	80	1500	100.0	2700K	Frosted	15,000	4.5	2.6	E26	3
<b>14W A19 • Non-Dimmable</b>													
L100A19N15V27K	LED 14W A19 ND 2700K Pro Line	14	100	80	1500	107.1	2700K	Frosted	15,000	4.5	2.6	E26	3
<b>LED BR • Dimmable • 15,000 Hour</b>													
L50R20D15V27K	LED 7W R20 DIM 2700K Pro Line	7.5	50	80	500	66.7	2700K	Frosted	15,000	3.8	2.5	E26	3
L65BR30D15V27K	LED 9W BR30 DIM 2700K Pro Line	9	65	80	665	73.9	2700K	Frosted	15,000	4.8	3.7	E26	3
L75BR40D15V27K	LED 14W BR40 DIM 2700K Pro Line	14	75	80	1065	76.1	2700K	Frosted	15,000	5.6	7.3	E26	3
<b>LED PAR* • Dimmable • 15,000 Hour</b>													
L50P20D15V30KFL	LED 7W P20 DIM 30KFL Pro Line	7	50	80	525	75	3000K	Frosted	15,000	3.4	2.3	E26	3
L75P30D15V30KFL	LED 10W P30 DIM 30KFL Pro Line	9	75	80	720	80	3000K	Frosted	15,000	4.8	3.9	E26	3
L90P38D15V30KFL	LED 13W P38 DIM 30KFL Pro Line	13	90	80	1100	84.6	3000K	Frosted	15,000	5.3	4.8	E26	3

\* ALL PAR LAMPS HAVE A 40° BEAM ANGLE AND ARE SUITABLE FOR WET LOCATIONS.