



LED Smooth Face Retrofit CCT Selectable Downlights

Product Specifications



TCP's LED Smooth Face Retrofit CCT Selectable Downlights are the perfect choice for new construction or remodeling projects. The slim, energy-efficient design is easy to install and offers a rated lifetime of 50,000 hours.

Reasons to choose the LED Smooth Face Retrofit CCT Selectable Downlights from TCP

- Mounts directly to recessed can (4", 5", or 6") includes integrated trim, pigtail and spring clips
- Easy installation
- Dimmable
- Slim, low-profile design
- Excellent color consistency
- Selectable CCT (27K/30K/35K) or (30K/40K/50K)
- 50,000 hour rated life
- UL approved for damp locations
- Back-lit technology
- IC rated

Ideal Applications

- Retrofits
- New construction
- Residential
- Office
- Retail
- Hospitality
- Drop ceilings
- Remodeling



Applications

Slim, low-profile design and easy retrofit installation makes these downlights ideal for 4" and 5"/6" new construction and retrofit applications.

Construction

Mounts directly to recessed can (4" or 5"/6") with integrated trim for easy installation, including pigtail and spring clips.

Electrical

- UL approved for damp locations
- Easy installation with integrated E26 base adapter
- 50,000 hour rated life

Optics

- Excellent color consistency
- Smooth, uniform dimming
- Highly-efficient LEDs and driver
- Triac dimming



Listings

cULus Listed and RoHS

Warranty

Five year limited warranty against defects in manufacturing.

LED Smooth Face Retrofit CCT Selectable Downlights

ITEM #	DESCRIPTION	VOLTAGE	INCAND. WATTS	WATTAGE	LUMENS	LPW	COLOR SELECTABLE	BEAM ANGLE	CRI	MOL (IN)	DIA (IN)
LEDDR4SFCCT1	4" SMOOTH FACE RETROFIT 27K/30K/35K	120	75	10	850	85	27K/30K/35K	90°	80	3	5
LEDDR4SFCCT2	4" SMOOTH FACE RETROFIT 30K/40K/50K	120	75	10	850	85	30K/40K/50K	90°	80	3	5
LDR56SFCCT1	5"/6" SMOOTH FACE RETROFIT 27K/30K/35K	120	85	16	1400	87.5	27K/30K/35K	100°	80	1.5	7.125
LDR56SFCCT2	5"/6" SMOOTH FACE RETROFIT 30K/40K/50K	120	85	16	1400	87.5	30K/40K/50K	100°	80	1.5	7.125

TCP Standard LED Lamps, LED Filament Lamps and TCP Downlights have been tested to work with the following dimmers:

BRAND	MODEL
LUTRON	AYCL-153P
	CTCL-153PD-H
	CTCL-53PD-H
	DV-600P
	DV-600PR-WH
	DV-603PH-WH
	DVCL-153P
	LGCL-153P
	MACL_153M
	MSCL-OP153M
	PD-6WCL
	SCL-153PR
	SELV-300P
	TGCL-153P
MRF2S-6ELV120-WH	
LEVITON	6811
	6602
	6631
	6672
	6672-L
	6674
	DSLO6
	IPL06
COOPER	DAL06P
	SAL06P

*Dimming compatibility tests are performed under a controlled lab environment. Field conditions may vary from this type of environment. Dimmers may differ by age and versions under the same item number which may affect compatibility. Compatibility may also extend beyond this list as TCP products should work with most C-L Type Triac Dimmers. TCP recommends trying a few dimmer-lamp combinations in an on-site test to ensure compatibility and performance before a major installation. If there's a dimmer not on this list we can perform a lab test for compatibility.

TECHNOLOGY CAST IN A BEAUTIFUL LIGHT

For over 20 years, TCP has been designing, developing and delivering energy-efficient lighting into the market. Thanks to our cutting-edge technology and manufacturing expertise, we have shipped billions of high quality lighting products. With TCP, you can count on a lighting product that is designed to meet the needs of the market - that transforms your surroundings and envelopes you in warmth - lighting that generates beauty with every flip of the switch.

Sales:

Date:

Model:

Project:

Rep:

Catalog Number:

Type:

Notes:



For more information on the quality and care TCP can deliver, call us at **800.324.1496** or visit tcp.com

325 Campus Dr. | Aurora, Ohio 44202 | P: 800.324.1496 | F: 877.487.0516