



# LED Recessed Retrofits

## Product Specifications



TCP's Dimmable Retrofit Kits are the perfect choice for new construction and retrofit opportunities when a sleek, integrated look is preferred.

### Reasons to choose the LED Recessed Retrofits from TCP

- 35,000 hour life minimizes replacement and maintenance costs
- Very low heat generation is perfect for sensitive display lighting
- Excellent color consistency and CRI enhance colors of focal point while maintaining uniformity throughout lighting installation
- Mounts directly to recessed can (4 or 5-6 inch) for easy installation with integrated trim, including pigtail and spring clips
- Shatter resistant
- Smooth, uniform dimming from 100 - 5%

### Ideal Applications

- Commercial
- Healthcare
- Residential
- Retail
- Industrial

### Specifications

Color Temperatures ..... 2700K, 3000K, 4100K, 5000K  
Wattage options ..... 12W, 11W, 10W, 9.5W, 9W  
Input Line Voltage ..... 120 VAC  
Input Line Frequency ..... 50/60Hz  
Lamp Life (rated) ..... 35,000 hours  
Minimum Starting Temp ..... -22°F/-30°C

Maximum Operating Temp ..... 104°F/40°C  
CRI ..... 80, 90  
IC-rated for direct contact with insulation  
UL approved for damp location (indoor only)—outdoor environment may cause yellowing of the white trim. This is not covered by warranty.

## Specifications



4 inch  
Recessed Retrofit



5/6 inch  
Recessed Retrofit



4 inch HiCRI  
Recessed Retrofit



5/6 inch HiCRI  
Recessed Retrofit



ITEM #	DESCRIPTION	VOLTAGE	LED WATTS	REPLACE- MENT	LUMENS	LPW	CRI	COLOR TEMP	MOL (inches)	DIA (inches)	CASE QTY
<b>5/6" Recessed Retrofits</b>											
<b>120 Watt Replacement • 35,000 Hour</b>											
LED14DR5627K	LED 5/6" 12W DIM 120W EQ - 2700K	120V	12	120	1250	104.2	80	2700K	3.0	7.4	6
LED14DR5630K	LED 5/6" 12W DIM 120W EQ - 3000K	120V	12	120	1300	108.3	80	3000K	3.0	7.4	6
LED14DR5641K	LED 5/6" 12W DIM 120W EQ - 4100K	120V	12	120	1300	108.3	80	4100K	3.0	7.4	6
LED14DR5650K	LED 5/6" 12W DIM 120W EQ - 5000K	120V	12	120	1350	112.5	80	5000K	3.0	7.4	6
<b>75 Watt Replacement • 35,000 Hour</b>											
LED11DR5627K	LED 5/6" 9.5W DIM 75W EQ - 2700K	120V	9.5	75	850	89.5	80	2700K	3.0	7.4	6
LED11DR5630K	LED 5/6" 9.5W DIM 75W EQ - 3000K	120V	9.5	75	850	89.5	80	3000K	3.0	7.4	6
LED11DR5641K	LED 5/6" 9.5W DIM 75W EQ - 4100K	120V	9.5	75	875	92.1	80	4100K	3.0	7.4	6
LED11DR5650K	LED 5/6" 9.5W DIM 75W EQ - 5000K	120V	9.5	75	900	94.7	80	5000K	3.0	7.4	6
<b>HiCRI • 65 Watt Replacement • 35,000 Hour</b>											
L11DR56D3527K95*	LED 5/6" 11W HiCRI DIM 65W EQ - 2700K	120V	11	65	700	63.6	90	2700K	3.125	7.4	6
L11DR56D3530K95*	LED 5/6" 11W HiCRI DIM 65W EQ - 3000K	120V	11	65	750	68.2	90	3000K	3.125	7.4	6
<b>4" Recessed Retrofits</b>											
<b>75 Watt Replacement • 35,000 Hour / 50,000 Hour*</b>											
LED10DR427K	LED 4" 10W DIM 75W EQ - 2700K	120V	10	75	750	75.0	80	2700K	3.0	5.0	6
LED10DR430K*	LED 4" 10W DIM 75W EQ - 3000K	120V	11	75	850	75.0	80	3000K	3.0	5.0	6
LED10DR441K	LED 4" 10W DIM 75W EQ - 4100K	120V	10	75	800	80.0	80	4100K	3.0	5.0	6
LED10DR450K	LED 4" 10W DIM 75W EQ - 5000K	120V	10	75	800	80.0	80	5000K	3.0	5.0	6
<b>HiCRI • 50 Watt Replacement • 35,000 Hour</b>											
L9DR4D3527K95*	LED 4" 9W HiCRI DIM 50W EQ - 2700K	120V	9	50	550	61.1	90	2700K	3.0	5.2	6
L9DR4D3530K95*	LED 4" 9W HiCRI DIM 50W EQ - 3000K	120V	9	50	600	66.7	90	3000K	3.0	5.2	6

\* All Plastic Body

# TECHNOLOGY CAST IN A BEAUTIFUL LIGHT

For over 30 years, TCP has been designing, developing and delivering energy-efficient lighting into the market. Thanks to our cutting-edge technology and manufacturing expertise, we have shipped billions of high quality lighting products. With TCP, you can count on a lighting product that is designed to meet the needs of the market - that transforms your surroundings and envelopes you in warmth - lighting that generates beauty with every flip of the switch.

Sales:

Date:

Model:

Project:

Rep:

Catalog Number:

Type:

Notes:



For more information on the quality and care TCP can deliver, call us at **800.324.1496** or visit [tcpi.com](http://tcpi.com)

325 Campus Dr. | Aurora, Ohio 44202 | P: 800.324.1496 | F: 877.487.0516