

TCP's Selectable Commercial Recessed Downlights offer choices for color temperatures and wattages, making these adaptable for many situations.

### Reasons to choose LED Selectable Commercial Recessed Downlights - Diffuser Version from TCP

- 3 selectable wattages
- Selectable colors (30K/35K/41K) or (27K/50K)
- 50,000 hour rated life minimizes replacement and maintenance costs
- Flicker-free design for consistent lighting
- Mounts directly to ceiling: 4, 6, 8, 10 or 12 inch
- Shatter resistant

- Easy installation and integrated trim
- Snap clips allow for installation without a recessed can
- 85° beam angle (4"/6"/8"/10")
- 70° beam angle (12′′)
- Smooth, uniform dimming 100 5%
- Matte silver and white finishes available

#### **Ideal Applications**

- Commercial
- Retail

- Industrial
- Healthcare

#### **Specifications**

-	
Color Temperatures	(30K/35K/41K) or (27K/30K)
Wattage Options	4" (7/9/12W), 6" (8/10/15W),
	(11/15/19W), 10" (18/23/30W),
	12" (18/23/30W)
Input Line Voltage	120-277V
Input Line Frequency	50/60Hz
	O-10V

Lamp Life (rated)	50,000 hours
Minimum Starting Temp	22°F/-30°C
Maximum Operating Temp	104°F/40°C
CRI	80

IC rated for direct contact with insulation

UL approved for damp locations











### LED Selectable Commercial Recessed Downlights Diffuser Version

#### **Specifications**



#### Selectable Commercial Recessed Downlight Diffuser Version (30K,35K,41K)

									LUMENS	;					
					LOW	EST WAT	TAGE	MIDI	OLE WAT	TAGE	HIGH	EST WAT	TAGE		
ITEM #	DESCRIPTION	VOLTAGE	INCAND. WATTS	WATTAGE	30K	35K	41K	30K	35K	41K	30K	35K	41K	LPW	CRI
4" Selectable Commercia	l Recessed D	ownligh	t – 65 '	Watt Rej	placer	nent (	50,0	000 H	lour						
DLC4SWUZDCCT (Matte Silver Finish) DLC4SWUZDCCTW (White Finish)	LED 4" Comm Downlight CCT	120-277	65	7/9/12	675	695	690	870	900	895	1150	1200	1190	LW: 96.4/99.3/98.6 MW: 96.7/100/99.4 HW: 95.8/100/99	80
6" Selectable Commercia	l Recessed D	ownligh	t – 85 '	Watt Rej	placer	nent (	50,0	000 H	lour						
DLC6SWUZDCCT (Matte Silver Finish) DLC6SWUZDCCTW (White Finish)	LED 6" Comm Downlight CCT	120-277	85	8/10/15	820	850	865	1030	1080	1095	1430	1530	1515	LW:103/106/108 MW:103/108/110 HW: 95/102/101	80
8" Selectable Commercia	l Recessed D	ownligh	t – 85 '	Watt Re <sub>l</sub>	placer	nent (	50,0	000 H	lour						
DLC8SWUZDCCT (Matte Silver Finish) DLC8SWUZDCCTW (White Finish)	LED 8" Comm Downlight CCT	120-277	85	11/15/19	1270	1300	1305	1720	1705	1775	2085	2150	2085	LW:115.5/118.2/119 MW:115/113.7/118.3 HW:110/113.2/110	80
10" Selectable Commerci	ial Recessed	Downlig	ht – 10	0 Watt	Repla	cemei	ıt • 5	0,00	) Hou	r					
DLC10SWUZDCCT (Matte Silver Finish) DLC10SWUZDCCTW (White Finish)	LED 10" Comm Downlight CCT	120-277	100	18/23/30	2100	2150	2150	2590	2660	2660	3205	3330	3305	LW:116.7/119.4/119.4 MW:112.6/115.7/115.7 HW:106.8/111/110.2	80
12" Selectable Commerci	ial Recessed	Downlig	ht – 12	5 Watt	Repla	cemei	ıt • 5	0,00	) Hou	r					
DLC12SWUZDCCT (Matte Silver Finish) DLC12SWUZDCCTW (White Finish)	LED 12" Comm Downlight CCT	120-277	125	18/23/30	2110	2160	2180	2650	2690	2690	3260	3380	3360	LW:117.2/120/121.1 MW:115.2/117/117 HW:108.7/112.7/112	80









### LED Selectable Commercial Recessed Downlights Diffuser Version

#### ecifications

#### Selectable Commercial Recessed Downlight Diffuser Version (27K,50K)

				,			LUA	MENS	,			
					LOWEST	WATTAGE	MIDDLE \	WATTAGE	HIGHEST	WATTAGE		
ITEM #	DESCRIPTION	VOLTAGE	INCAND. WATTS	WATTAGE	27K	50K	27K	50K	27K	50K	LPW	CRI
4" Selectable Commercial	Recessed Downl	ight Dif	fuser V	ersion –	65 Wa	tt Replo	cement	• 50,00	00 Hour			
DLC4SWUZDCCT2 (Matte Silver Finish) DLC4SWUZDCCT2W (White Finish)	LED 4" Comm Downlight Diffuser CCT	120-277	65	7/9/12	700	750	900	1000	1200	1300	LW:100/107.1 MW:100/111.1 HW:100/108.3	80
6" Selectable Commercial	Recessed Down	ight Dif	fuser V	ersion –	85 Wa	tt Replo	cement	• 50,00	00 Hour			
DLC6SWUZDCCT2 (Matte Silver Finish) DLC6SWUZDCCT2W (White Finish)	LED 6" Comm Downlight Diffuser CCT	120-277	85	8/10/15	700	750	1000	1050	1450	1500	LW: 87.5/93.8 MW:100/105 HW: 96.7/100	80
8" Selectable Commercial	Recessed Downl	ight Dif	fuser V	ersion –	85 Wa	tt Replo	cement	• 50,00	00 Hour			
DLC8SWUZDCCT2 (Matte Silver Finish) DLC8SWUZDCCT2W (White Finish)	LED 8" Comm Downlight Diffuser CCT	120-277	85	11/15/19	1200	1300	1600	1650	2000	2050	LW:109.1/118.2 MW:106.7/110 HW:105.3/107.9	80
10" Selectable Commercia	al Recessed Dow	nlight D	iffuser	Version -	- 100 V	Watt Re	placeme	ent • 50	,000 Ho	ur		
DLC10SWUZDCCT2 (Matte Silver Finish) DLC10SWUZDCCT2W (White Finish)	LED 10" Comm Downlight Diffuser CCT	120-277	100	18/23/30	1800	1850	2250	2300	2850	2950	LW:100/102.8 MW: 97.8/100 HW: 95/98.3	80
12" Selectable Commercia	al Recessed Dow	nlight D	iffuser	Version -	- 125 V	Watt Re	placeme	ent • 50	,000 Ha	our		
DLC12SWUZDCCT2 (Matte Silver Finish) DLC12SWUZDCCT2W (White Finish)	LED 12" Comm Downlight Diffuser CCT	120-277	125	18/23/30	1800	1850	2250	2300	2850	2950	LW:100/102.8 MW: 97.8/100 HW: 95/98.3	80










## LED Selectable Commercial Recessed Downlights Diffuser Version

#### Accessories

PRODUCT	ITEM NUMBER	DESCRIPTION	DIMENSIONS
	46INFRAMEKIT	4"/6" ADJUSTABLE FRAME KIT (Compatible with 4" and 6" downlights)	-
No.	EMBACKUPCOMDL1	EMERGENCY BACKUP FOR 4" AND 6" SELECTABLE COMMERCIAL DOWNLIGHT	9.45" X 1.77" X 1.18"
	EMBACKUPCOMDL2	EMERGENCY BACKUP FOR 8", 10" AND 12" SELECTABLE COMMERCIAL DOWNLIGHT	12.9" X 2.6" X 2.2"

#### **Dimensions**

Α	В	С	Item Number
5"	6.2"	4.5"	DLC4SWUZDCCT / DLC4SWUZDCCT2 / DLC4SWUZDCCTW / DLC4SWUZDCCT2W
6.4"	7.8"	5.6"	DLC6SWUZDCCT / DLC6SWUZDCCT2 / DLC6SWUZDCCTW / DLC6SWUZDCCT2W
7.4"	9.2"	7.3"	DLC8SWUZDCCT / DLC8SWUZDCCT2 / DLC8SWUZDCCTW / DLC8SWUZDCCT2W
8.2"	10.9"	9"	DLC10SWUZDCCT / DLC10SWUZDCCT2 / DLC10SWUZDCCTW / DLC10SWUZDCCT2W
9.5"	13"	11"	DLC12SWUZDCCT / DLC12SWUZDCCT2 / DLC12SWUZDCCTW / DLC12SWUZDCCT2W



For the most up-to-date specs, please visit www.tcpi.com









# TECHNOLOGY CAST IN A BEAUTIFUL LIGHT

For over 30 years, TCP has been designing, developing and delivering energy-efficient lighting into the market. Thanks to our cutting-edge technology and manufacturing expertise, we have shipped billions of high quality lighting products. With TCP, you can count on a lighting product that is designed to meet the needs of the market - that transforms your surroundings and envelopes you in warmth - lighting that generates beauty with every flip of the switch.

Sales:	Catalog Number:
Date:	Туре:
Model:	Notes:
Project:	<b>OTCP</b>
Rep:	we know light.™