



Allusion LED Line with Smooth Warm Dimming



Introducing TCP's latest offering of Allusion LED Line—the "incandescentlike" LEDs that offer a unique dimming profile, replicating true incandescent/halogen dimming.

Reasons to choose the Allusion LED Lamps from TCP

- Instant energy savings - up to 85% more efficient than incandescent/halogen replacements
- Long life of 25,000/30,000 (SL16) hours minimizes replacement and maintenance costs
- Smooth warm dimming creates the perfect atmosphere
- UL approved for damp locations* - can be used outdoors when protected from elements. Can withstand humidity indoors/outdoors
- Shatter resistance lowers the risk of injury and breakage

Ideal Applications

- Table Lamps
- Floor Lamps
- Sconces
- Ceiling Fixtures
- Chandeliers
- Decorative
- Track Lights
- Recessed Downlights

Specifications

Voltage 120VAC/ 12 VAC (MR16)
 Input Line Frequency..... 50/60Hz
 Lamp Life (Rated)25,000/30,000 (SL16)
 Minimum Starting Temp-22°F/-30°C
 Maximum Operating Temp.....45°C

CRI..... 80
 Color Temperatures..... 3000K to 2000K/
 3000K to 1800K (MR16/DL)/
2700K to 2000K (A19)

Specifications



| ITEM # | DESCRIPTION | VOLTAGE | LED WATTS | WATTAGE EQUIVALENT | LUMENS | LPW | CRI | COLOR TEMPERATURE | BEAM ANGLE | MOL (inches) | DIA (inches) | BASE |
|--|---|---------|-----------|--------------------|--------|-------|-----|-------------------|------------|--------------|--------------|------|
| LED A19 60W Equivalent | | | | | | | | | | | | |
| LED9A19DA | LED 9W A19 27K Allusion | 120V | 9 | 60 | 650 | 72.2 | >80 | 2700K to 2000K | - | 4.6 | 2.4 | E26 |
| LED BR30 65W Equivalent | | | | | | | | | | | | |
| LED10BR30DA | LED 10W BR30 27K Allusion | 120V | 10 | 65 | 675 | 67.5 | >80 | 3000K to 2000K | - | 5.4 | 3.8 | E26 |
| LED PAR38 90W Equivalent | | | | | | | | | | | | |
| L15P38DNFLA | LED 15W PAR38 30K Allusion NFL | 120V | 12.5 | 90 | 975 | 78.00 | >80 | 3000K to 2000K | 25° | 5.4 | 4.75 | E26 |
| L15P38DFLA | LED 15W PAR38 30K Allusion FL | 120V | 12.5 | 90 | 975 | 78.00 | >80 | 3000K to 2000K | 40° | 5.4 | 4.75 | E26 |
| LED PAR38 100W Equivalent • PHASE OUT | | | | | | | | | | | | |
| LED15P38DA | LED 15W PAR38 30K Allusion NFL | 120V | 15 | 100 | 975 | 65 | >80 | 3000K to 2000K | 25° | 5.4 | 4.75 | E26 |
| LED PAR30 90W Equivalent | | | | | | | | | | | | |
| L15P30DNFLA | LED 15W PAR30 30K Allusion NFL | 120V | 12.5 | 90 | 950 | 76.00 | >80 | 3000K to 2000K | 25° | 4.7 | 3.8 | E26 |
| L15P30DFLA | LED 15W PAR30 30K Allusion FL | 120V | 12.5 | 90 | 950 | 76.00 | >80 | 3000K to 2000K | 40° | 4.7 | 3.8 | E26 |
| LED PAR20 50W Equivalent | | | | | | | | | | | | |
| L7P20DNFLA | LED 7W PAR20 30K Allusion NFL | 120V | 6.5 | 50 | 525 | 80.77 | >80 | 3000K to 2000K | 25° | 3.4 | 2.5 | E26 |
| L7P20DFLA | LED 7W PAR20 30K Allusion FL | 120V | 6.5 | 50 | 525 | 80.77 | >80 | 3000K to 2000K | 40° | 3.4 | 2.5 | E26 |
| LED MR16 35W Equivalent | | | | | | | | | | | | |
| L712VMR16DNFLA | LED 7W MR16 30K Allusion NFL | 12V | 6 | 35 | 350 | 58.33 | >80 | 3000K to 1800K | 20° | 1.9 | 2.0 | E3 |
| LED SL16 Starlight | | | | | | | | | | | | |
| L15SL16D30A | LED 13W SL16 30K Allusion | 120V | 13 | - | 1200 | 92.30 | >80 | 3000K to 2000K | 110° | 3.8 | 6.3 | E26 |
| LED 5"/6" Downlight 65W Equivalent | | | | | | | | | | | | |
| LED10DR56DA | LED 11W 5"/6" Recessed Downlight Allusion | 120V | 11 | 65 | 1100 | 100 | >80 | 3000K to 1800K | - | 3.0 | 7.5 | E26 |

For the most up-to-date specs, please visit www.tcpi.com

TCP®

325 Campus Dr. | Aurora, Ohio 44202 | P: 800-324-1496 | tcpi.com



PAR38, PAR30 and PAR20 lamps UL approved for wet location



RoHS
COMPLIANT

5 YEAR
WARRANTY

*Troffer warranty is 5yrs/50,000hrs

Dimmer Compatibility

| E26 SUGGESTED DIMMER COMPATIBILITY | |
|------------------------------------|----------------|
| MANUFACTURER | MODEL NUMBER |
| Leviton | R50-IPLO6-10M |
| | R61-06674-POI |
| Lutron | CTCL-153PDH-WH |
| | TGCL-153PH-WH |
| | DVWCL-153PH-WH |

| MR16 SUGGESTED DIMMER COMPATIBILITY | |
|-------------------------------------|--------------------------|
| MANUFACTURER | MODEL NUMBER |
| Leviton | Sureslide 6615P |
| Lutron | Diva DVLV-600P |
| | Divs DVELV-300P |
| | Skylark SLEV-300P |
| | Skylark SLV-600P |
| | Nova NELV-450 |
| | Nova NTELV-600 |
| | MAIV-600 |
| | VERTI VTELV-600M |
| Cooper | DAL06P - All load dimmer |
| | SAL06P |

For the most up-to-date specs, please visit www.tcpi.com

TCP®

325 Campus Dr. | Aurora, Ohio 44202 | P: 800-324-1496 | tcpi.com

©TCP MAY 2024/NF225757



PAR38, PAR30 and PAR20 lamps UL approved for wet location



RoHS COMPLIANT

5 YEAR WARRANTY

*Troffer warranty is 5yrs/50,000hrs

TECHNOLOGY CAST IN A BEAUTIFUL LIGHT

For over 30 years, TCP has been designing, developing and delivering energy-efficient lighting into the market. Thanks to our cutting-edge technology and manufacturing expertise, we have shipped billions of high quality lighting products. With TCP, you can count on a lighting product that is designed to meet the needs of the market - that transforms your surroundings and envelopes you in warmth - lighting that generates beauty with every flip of the switch.

Sales:

Date:

Model:

Project:

Rep:

Catalog Number:

Type:

Notes:



For more information on the quality and care TCP can deliver, call us at **800.324.1496** or visit tcp.com

325 Campus Dr. | Aurora, Ohio 44202 | P: 800.324.1496 | F: 877.487.0516