



LED Classic Filament Globe Lamps

Dimmable

Omnidirectional

15,000 Hours

TCP's filament style LED globe lamps provide all the beauty and style of traditional decorative lamps with the energy and cost savings of LED. Exclusive LED technology provides unmatched longevity and perfect 5-100% dimming.

Reasons to choose the LED Classic Filament Globe Lamps from TCP

- Uses up to 85% less energy than halogen alternatives
- Unique filament - LED configuration provides uniform color output
- Smooth, uniform dimming
- Long life minimizes replacement and maintenance costs
- UL approved for damp and enclosed locations
- ANSI construction compliant fits most general applications

Ideal Applications

- Accent Lighting
- Chandeliers
- Wall Sconces
- Ceiling Fans
- Decorative Lighting

Specifications:

Color Temperatures.....2200K, 2700K, 3000K,
4000K, 5000K
Input Line Voltage 120 VAC Input Line
Frequency 50/60HZ
Lamp Life (Rated) 15,000 hours

Minimum Starting Temp -30°C
Maximum Operating Temp..... 40°C
CRI >80
Base E12 & E26
Warranty 3 Years

TCP® LED Classic Filament Globe Lamps

Specifications:



**25/40W G16
E12 CLEAR**



**25/40W G16
E12 FROSTED**



**25/40W G16
E26 CLEAR**



**25/40W G16
E26 FROSTED**



**40W G25
E26 CLEAR**



**40W G25
E26 FROSTED**



**40/60W G25
E26 FROSTED**



**40/60W G25
E26 CLEAR**



**40W G25
E26 SILVER BOWL**

TCP LED Classic Filament Globe Lamps

Specifications:

ITEM #	DESCRIPTION	LED WATTS	INCAND. WATTS	LUMENS	CRI	COLOR TEMP	GLASS TYPE	MOL (INCHES)	DIA. (INCHES)	BASE
Filament G16 Globe • 25 Watt Replacements • Dimmable • E12 Base • 15,000 Hour										
FG16D2530EE12C	G16 25W 3000K CLEAR E12	3.0	25	250	>80	3000K	Clear	3.4	2.0	E12
FG16D2550EE12W	G16 25W 5000K FROSTED E12	3.0	25	250	>80	5000K	Frosted	3.4	2.0	E12
Filament G16 Globe • 25 Watt Replacements • Dimmable • E26 Base • 15,000 Hour										
FG16D2522KC	G16 25W 2200K CLEAR E26	3.0	25	225	>80	2200K	Clear	3.3	2.0	E26
FG16D2522KW	G16 25W 2200K FROSTED E26	3.0	25	225	>80	2200K	Frosted	3.3	2.0	E26
FG16D2527EW	G16 25W 2700K FROSTED E26	3.0	25	250	>80	2700K	Frosted	3.3	2.0	E26
FG16D2550EC	G16 25W 5000K CLEAR E26	3.0	25	250	>80	5000K	Clear	3.3	2.0	E26
FG16D2550EW	G16 25W 5000K FROSTED E26	3.0	25	250	>80	5000K	Frosted	3.3	2.0	E26
Filament G16 Globe • 40 Watt Replacements • Dimmable • E12 Base • 15,000 Hour										
FG16D4022KE12C	G16 40W 2200K CLEAR E12	4.0	40	325	>80	2200K	Clear	3.4	2.0	E12
FG16D4022KE12W	G16 40W 2200K FROSTED E12	4.0	40	325	>80	2200K	Frosted	3.4	2.0	E12
FG16D4050EE12W	G16 40W 5000K FROSTED E12	4.0	40	350	>80	5000K	Frosted	3.4	2.0	E12
Filament G16 Globe • 40 Watt Replacements • Dimmable • E26 Base • 15,000 Hour										
FG16D4022KW	G16 40W 2200K FROSTED	4.0	40	325	>80	2200K	Frosted	3.3	2.0	E26
FG16D4027EW	G16 40W 2700K FROSTED	4.0	40	350	>80	2700K	Frosted	3.3	2.0	E26
FG16D4050EC	G16 40W 5000K CLEAR	4.0	40	350	>80	5000K	Clear	3.3	2.0	E26
FG16D4050EW	G16 40W 5000K FROSTED	4.0	40	350	>80	5000K	Frosted	3.3	2.0	E26
Filament G25 Globe • 40 Watt Replacements • Dimmable • E26 Base • 15,000 Hour										
FG25D4022KC	G25 40W 2200K CLEAR	4.0	40	295	>80	2200K	Clear	4.5	3.2	E26
FG25D4022KW	G25 40W 2200K FROSTED	4.0	40	295	>80	2200K	Frosted	4.5	3.2	E26
FG25D4027SB	G25 40W 2700K SILVER BOWL	4.0	40	300	>80	2700K	Clear	4.5	3.2	E26
FG25D4050EC	G25 40W 5000K CLEAR	4.0	40	350	>80	5000K	Clear	4.5	3.2	E26
Filament G25 Globe • 60 Watt Replacements • Dimmable • E26 Base • 15,000 Hour										
FG25D6022KC	G25 60W 2200K CLEAR	5.0	60	475	>80	2200K	Clear	4.5	3.2	E26
FG25D6022KW	G25 60W 2200K FROSTED	5.0	60	475	>80	2200K	Frosted	4.5	3.2	E26
FG25D6050EC	G25 60W 5000K CLEAR	5.0	60	500	>80	5000K	Clear	4.5	3.2	E26
FG25D6050EW	G25 60W 5000K FROSTED	5.0	60	500	>80	5000K	Frosted	4.5	3.2	E26
High Output Filament G25 Globe • 100 Watt Replacements • Dimmable • E26 Base • 15,000 Hour										
FG25DHL27KEC	G25 60W 2700K HO CLEAR	8.0	100	800	>80	2700K	Clear	4.7	3.2	E26
Filament G40 Globe • 40 Watt Replacements • Dimmable • E26 Base • 15,000 Hour										
FG40D4022EC	G40 40W 2200K E26 CLEAR	4.5	40	450	>80	2200K	Clear	6.5	4.9	E26
FG40D4030EC	G40 40W 3000K E26 CLEAR	4.5	40	450	>80	3000K	Clear	6.5	4.9	E26

Suggested Dimmer Compatibility

Manufacturer	Model Number
Leviton	R50-IPLO6-10M
Leviton	R61-06674-POI
Lutron	CTCL-153PDH-VWH
Lutron	TGCL-153PH-VWH
Lutron	DWWCL-153PH-VWH

For the most up-to-date specs, please visit www.tcpi.com

TCP®

325 Campus Dr. | Aurora, Ohio 44202 | P: 800-324-1496 | tcpi.com

©TCP APR 2024/WF 280752



RoHS
COMPLIANT

3 YEAR
WARRANTY

*Based on 12 hours use per day

TECHNOLOGY CAST IN A BEAUTIFUL LIGHT

For over 30 years, TCP has been designing, developing and delivering energy-efficient lighting into the market. Thanks to our cutting-edge technology and manufacturing expertise, we have shipped billions of high quality lighting products. With TCP, you can count on a lighting product that is designed to meet the needs of the market - that transforms your surroundings and envelopes you in warmth - lighting that generates beauty with every flip of the switch.

Sales:

Date:

Model:

Project:

Rep:

Catalog Number:

Type:

Notes:



For more information on the quality and care TCP can deliver, call us at **800.324.1496** or visit tcpi.com

325 Campus Dr. | Aurora, Ohio 44202 | P: 800.324.1496 | F: 877.487.0516