



Pro Line Family of LED Lamps

Product Specifications



For an affordable LED upgrade, switch to TCP's Pro Line LED Lamps. Pro Line LEDs are available in multiple options from A-Lamps, to BR30 and PAR38 lamps. See how you can maximize savings and minimize maintenance costs with Pro Line LED Lamps.

Reasons to choose the Pro Line from TCP

- Long life: 15,000 hours minimizes replacement and maintenance costs
- Inexpensive alternative for cost-sensitive projects
- ANSI Construction Compliant to fit most general applications
- UL approved for damp location means lamps can be used outdoors when protected from the elements. (All PAR lamps are suitable for wet locations.)

Ideal Applications

- Commercial
- Retail
- Industrial
- Residential

Specifications

| | | | |
|------------------------------|--------------|--|---------|
| Input Line Voltage | 120 VAC | CRI | 80 |
| Input Line Frequency | 50/60HZ | Warranty | 3 Years |
| Lamp Life (Rated) | 15,000 hours | * All A-Lamps, Deco, and R/BR Floods are approved for use in Enclosed Luminaires | |
| Minimum Starting Temp | -22°F/-30°C | * PARs are not recommended for use in Enclosed Luminaires | |
| Maximum Operating Temp | 104°F/40°C | | |



Specifications



| ITEM # | DESCRIPTION | WATTS | INCAND. WATTS | CRI | LUMENS | LPW | COLOR | FINISH | HOURS | MOL (inches) | DIA (inches) | BASE | WARRANTY YEARS |
|---|---------------------------------|-------|---------------|-----|--------|-------|-------|--------|--------|--------------|--------------|------|----------------|
| LED All Glass A-LAMP • 15,000 Hour | | | | | | | | | | | | | |
| 4.5W A19 • Dimmable | | | | | | | | | | | | | |
| LFF40A19D1527K | LED 40W EQ GLASS A19 DIM 27K FR | 4.5 | 40 | 80 | 425 | 94.4 | 2700K | FROST | 15,000 | 4.2 | 2.4 | E26 | 3 |
| LFC40A19D1527K | LED 40W EQ GLASS A19 DIM 27K CL | 4.5 | 40 | 80 | 425 | 94.4 | 2700K | CLEAR | 15,000 | 4.2 | 2.4 | E26 | 3 |
| 5W A19 • Non-Dimmable | | | | | | | | | | | | | |
| LFF40A19N1527K | LED 40W EQ GLASS A19 ND 27K FR | 5 | 40 | 80 | 425 | 85.0 | 2700K | FROST | 15,000 | 4.2 | 2.4 | E26 | 3 |
| LFF40A19N1550K | LED 40W EQ GLASS A19 ND 50K FR | 5 | 40 | 80 | 425 | 85.0 | 5000K | FROST | 15,000 | 4.2 | 2.4 | E26 | 3 |
| LFC40A19N1527K | LED 40W EQ GLASS A19 ND 27K CL | 5 | 40 | 80 | 425 | 85.0 | 2700K | CLEAR | 15,000 | 4.2 | 2.4 | E26 | 3 |
| LFC40A19N1550K | LED 40W EQ GLASS A19 ND 50K CL | 5 | 40 | 80 | 425 | 85.0 | 5000K | CLEAR | 15,000 | 4.2 | 2.4 | E26 | 3 |
| 8W A19 • Dimmable | | | | | | | | | | | | | |
| LFF60A19D1550K | LED 60W EQ GLASS A19 DIM 50K | 8 | 60 | 80 | 725 | 90.6 | 5000K | FROST | 15,000 | 4.2 | 2.4 | E26 | 3 |
| 8W A19 • Non-Dimmable | | | | | | | | | | | | | |
| LFC60A19N1527K | LED 60W EQ GLASS A19 ND 27K CL | 8 | 60 | 80 | 725 | 90.6 | 2700K | CLEAR | 15,000 | 4.2 | 2.4 | E26 | 3 |
| LFC60A19N1550K | LED 60W EQ GLASS A19 ND 50K CL | 8 | 60 | 80 | 725 | 90.6 | 5000K | CLEAR | 15,000 | 4.2 | 2.4 | E26 | 3 |
| LED All Glass Decorative 40W Equivalent • Dimmable • 15,000 Hour | | | | | | | | | | | | | |
| FG25D40V27W | LED 4W G25 DIM 27K FR PRO LINE | 4 | 40 | 80 | 350 | 87.5 | 2700K | FROST | 15,000 | 4.5 | 3.2 | E26 | 3 |
| LED A-LAMP • 15,000 Hour | | | | | | | | | | | | | |
| 9W A19 • Non-Dimmable | | | | | | | | | | | | | |
| L60A19N15V27K | LED 9W A19 ND 27K PRO LINE | 9 | 60 | 80 | 800 | 88.9 | 2700K | FROST | 15,000 | 4.3 | 2.4 | E26 | 3 |
| 14W A19 • Non-Dimmable | | | | | | | | | | | | | |
| L100A19N15V27K | LED 14W A19 ND 27K PRO LINE | 14 | 100 | 80 | 1500 | 107.1 | 2700K | FROST | 15,000 | 4.5 | 2.6 | E26 | 3 |
| LED BR • Dimmable • 15,000 Hour | | | | | | | | | | | | | |
| L50R20D15V27K | LED 7W R20 DIM 27K PRO LINE | 7.5 | 50 | 80 | 500 | 66.7 | 2700K | FROST | 15,000 | 3.8 | 2.5 | E26 | 3 |
| L65BR30D15V27K | LED 9W BR30 DIM 27K PRO LINE | 9 | 65 | 80 | 665 | 73.9 | 2700K | FROST | 15,000 | 4.8 | 3.7 | E26 | 3 |
| L75BR40D15V27K | LED 14W BR40 DIM 27K PRO LINE | 14 | 75 | 80 | 1065 | 76.1 | 2700K | FROST | 15,000 | 5.6 | 7.3 | E26 | 3 |
| LED PAR* • Dimmable • 15,000 Hour | | | | | | | | | | | | | |
| L50P20D15V30KFL | LED 7W P20 DIM 30K FL PRO LINE | 7 | 50 | 80 | 525 | 75 | 3000K | FROST | 15,000 | 3.4 | 2.3 | E26 | 3 |
| L75P30D15V30KFL | LED 10W P30 DIM 30K FL PRO LINE | 9 | 75 | 80 | 720 | 80 | 3000K | FROST | 15,000 | 4.8 | 3.9 | E26 | 3 |
| L90P38D15V30KFL | LED 13W P38 DIM 30K FL PRO LINE | 13 | 90 | 80 | 1100 | 84.6 | 3000K | FROST | 15,000 | 5.3 | 4.8 | E26 | 3 |

* ALL PAR LAMPS HAVE A 40° BEAM ANGLE AND ARE SUITABLE FOR WET LOCATIONS.

| SUGGESTED DIMMER COMPATIBILITY | |
|--------------------------------|----------------|
| MANUFACTURER | MODEL NUMBER |
| Leviton | R50-PL06-10M |
| | R61-06674-POI |
| Lutron | CTCL-153PDH-WH |
| | TGCL-153PH-WH |
| | DWVCL-153PH-WH |

Note: E26 compatible dimmer



TECHNOLOGY CAST IN A BEAUTIFUL LIGHT

For over 30 years, TCP has been designing, developing and delivering energy-efficient lighting into the market. Thanks to our cutting-edge technology and manufacturing expertise, we have shipped billions of high quality lighting products. With TCP, you can count on a lighting product that is designed to meet the needs of the market - that transforms your surroundings and envelopes you in warmth - lighting that generates beauty with every flip of the switch.

Sales:

Date:

Model:

Project:

Rep:

Catalog Number:

Type:

Notes:



For more information on the quality and care TCP can deliver, call us at **800.324.1496** or visit tcp.com

325 Campus Dr. | Aurora, Ohio 44202 | P: 800.324.1496 | F: 877.487.0516