



LED Lamps with Smooth Warm Dimming

Product Specifications



Introducing TCP's Allusion "incandescent-like" LED smooth warm dimming technology. LEDs with a unique dimming profile that replicates true incandescent/halogen dimming.

Reasons to choose the Allusion LED Lamps from TCP

- Dimming Range (CCT):
 - A19 – 2700K to 2000K
 - B11 – 2400K to 1900K
 - BR30 – 3000K to 2000K
 - PAR30 – 3000K to 2000K
 - PAR38 – 3000K to 2000K
 - 5"/6" Downlight – 3000K to 1800K
- Energy efficient: Up to 85% more efficient than incandescent/halogen replacements
- Long life: 25,000 hours
- Similar look and feel as incandescent alternative
- Approved for damp locations

Ideal Applications

- Table Lamps
- Floor Lamps
- Sconces
- Ceiling Fixtures
- Decorative Lighting
- Chandeliers
- Recessed Downlights
- Track Lights
- Dimmable 6" & 5" Downlight applications

Specifications:

Voltage 120 VAC
Input Line Frequency 50/60HZ
Lamp Life (Rated) 25,000 hours
Minimum Starting Temp -30°C
Maximum Operating Temp 40°C

CRI 80
Beam Angle 25° (PAR30, PAR38)
Base E12, E26
Warranty 5 Years
Suitable for use in totally enclosed fixtures



LED Lamps with Smooth Warm Dimming

Specifications:



A19



B10



BR30



PAR30



PAR38



5"/6" Recessed Downlight

ITEM #	DESCRIPTION	VOLTAGE	WATTS	REPLACEMENT WATTS	LUMENS	LPW	BEAM ANGLE	CCT	CRI	R9	MOL (inches)	DIA (inches)
TCP Allusion LED Lamps												
LED9A19DA	9W A19 A-Lamp	120	9	60	650	72.2	OMNI	2700K to 2000K	80	>0	4.6	2.4
LED5E12B11DA	5W B11 Candelabra Blunt Tip	120	5	25	300	60.0	OMNI	2400K to 1900K	80	>0	3.8	1.4
LED5E12B11DAF	5W B11 Candelabra Blunt Tip Frost	120	5	25	300	60.0	OMNI	2400K to 1900K	80	>0	3.8	1.4
LED10BR30DA	10W BR30	120	10	65	675	67.5	OMNI	3000K to 2000K	80	>0	5.4	3.8
LED15P30DA	15W PAR30	120	15	100	950	63.3	25°	3000K to 2000K	80	>0	5.2	4.8
LED15P38DA	15W PAR38	120	15	100	975	65.0	25°	3000K to 2000K	80	>0	5.2	4.8
LED10DR56DA	11W 5"/6" Recessed Downlight	120	11	65	1100	100.0		3000K to 1800K	80	>0	3.0	7.5

TCP®

325 Campus Dr. | Aurora, Ohio 44202 | P: 800-324-1496 | tcp.com

©TCP MAY 2025/WF103409



RoHS
COMPLIANT

5 YEAR
WARRANTY