



# LED Elevator Lamps

## Product Specifications



TCP's LED elevator lamps are designed for rough service applications. Utilizing a shatter resistant polycarbonate lens and overall robust design, TCP LED elevator lamps are durable and built to withstand the vibration and motion of elevators.

### Reasons to choose LED Elevator Lamps from TCP

- Uses 90% less energy than standard incandescent replacements
- 25,000 hours (lasts at least 15 times longer than alternative)
- More overall light output compared to incandescent
- Very low heat generation in cab as compared to incandescent lamps
- Shatter resistant polycarbonate lens
- Very low heat generation in cab as compared to incandescent lamps

### Ideal Applications

- Elevators

### Specifications

Voltage ..... 12V  
 Input Line Frequency..... 50/60Hz  
 Lamp Life (Rated) ..... 25,000 hours  
 Minimum Starting Temp ..... -4°F/-20°C

Maximum Operating Temp..... 104°F/40°C  
 Dimmable ..... No  
 Warranty ..... 3 Years

## Specifications



LED2W1383V2



LED2WGBFV2

ITEM #	DESCRIPTION	WATTS	LUMENS	COLOR TEMP	BASE	CRI	VOLTAGE	RATED LIFE	CASE QTY
LED2W1383V2	2W 1383 Elevator Lamp - 2700K, Frosted	2W	150	2700K	BA15S	80	12V	25,000 Hours	12
LED2WGBFV2	2W GBF Elevator Lamp - 2700K, Frosted	2W	150	2700K	BA15D	80	12V	25,000 Hours	12

# TECHNOLOGY CAST IN A BEAUTIFUL LIGHT

For over 30 years, TCP has been designing, developing and delivering energy-efficient lighting into the market. Thanks to our cutting-edge technology and manufacturing expertise, we have shipped billions of high quality lighting products. With TCP, you can count on a lighting product that is designed to meet the needs of the market - that transforms your surroundings and envelopes you in warmth - lighting that generates beauty with every flip of the switch.

Sales:

Date:

Model:

Project:

Rep:

Catalog Number:

Type:

Notes:



For more information on the quality and care TCP can deliver, call us at **800.324.1496** or visit [tcp.com](http://tcp.com)

325 Campus Dr. | Aurora, Ohio 44202 | P: 800.324.1496 | F: 877.487.0516