

The TCP Select Series LED Vapor Tight Luminaire is perfect for your wet location low bay needs. Providing ample light at a low energy cost, the Vapor Tight is ready for the worst weather. With a plastic housing and included mounting hardware, the TCP Select Series LED Vapor Tight is durable and quick to install.

Reasons to choose the Select Series LED Vapor Tight from TCP

- Durable plastic housing
- Frosted PC lens for glare control
- Wet location rated

- Long life: 50,000 hours rated life
- Operating temperature: -11°F to 122°F
- Wide beam spread

Ideal Applications

- Parking Garages
- Car Washes
- Cold Storage
- Garden Centers

- Corridors
- Stairwells
- Hallways









Select Series LED Vapor Tight

Specifications

Lumens	
SW2 Package:	
2 ft	2500/3000/4200L
4 ft	
8 ft	4200/5200/6000L
SW4 Package:	
0	4200/5200/6000L
SW5 Package:	, ,
~	6000/7200/8500L
Wattage	
SW2 Package:	
	18/22/32W
	18/22/32W
SW4 Package:	
_	20 /40 /4/\\
SW5 Package:	
8 ft	45/55/65W
Lumens per Watt (LPW)	>130 LPVV
Color Temperature (CCT).	35/40/50K Selectable
Controls	Occupancy sensor w/ daylight harvesting (optional)
	O-10V (standard)
•	>50,000 hours
Naida Ello	

Item Number	
Notes	Туре

IP65	
Operating Temperature	24°C to 50°C
CRI	80+
Onwar Egytor	× 0.0

Warranty

Five year limited warranty against

defects in manufacturing.

Features

Listings

UL and cUL listed

RoHS Compliant

- Durable lens and housing
- -24°C (-11°F) to 50°C (122°F) operating range
- Stainless steel clips allow for easy lens removal

Catalog Ordering Matrix Example: VTF2UZDSW2CCT								
FAMILY	SIZE	VOLTAGE	DIMMING	LUMEN PACKAGE ¹	WATTAGE ²	COLOR TEMPERATURE	FACTORY INSTALLED OPTIONS	OPTIONAL SENSOR CONTROLS
SELECTABLE WAT	SELECTABLE WATTAGE WITH SELECTABLE CCT							
	2 – 2 feet			SW2 - 2500/3000/4200L	18/22/32W			
VTF - Vapor Tight Fixture		ZD – 0-10V Dimming	SW2 – 2500/3000/4200L SW4 – 4200/5200/6000L SW5 – 6000/7200/8500L	18/22/32W 32/40/46W 45/55/65W	CCT – 35K/40K/50K Selectable Color	BLANK – No Controls EB –	BLANK – No Controls LS1 – PIR Motion Sensor LS1D – PIR/Daylight Sensor IS – Integrated Sensor	
	8 – 8 foot			SW2 – 4200/5200/6000L SW5 – 6000/7200/8500L	32/40/46W 45/55/65W		Battery Backup	NLS - Network Lighting Sensor

² Actual wattage may differ by +/- 10%.












¹Approximate lumen output. Actual performance may vary based on CCT, options selected and end user application.



Select Series LED Vapor Tight

Dimensions



Spacing Criterion (0-180): 1.22 Spacing Criterion (90-270): 1.22









©TCP MAY 2025/WF517750

325 Campus Dr. | Aurora, Ohio 44202 | P: 800-324-1496 | tcpi.com

TECHNOLOGY CAST IN A BEAUTIFUL LIGHT

For over 30 years, TCP has been designing, developing and delivering energy-efficient lighting into the market. Thanks to our cutting-edge technology and manufacturing expertise, we have shipped billions of high quality lighting products. With TCP, you can count on a lighting product that is designed to meet the needs of the market - that transforms your surroundings and envelopes you in warmth - lighting that generates beauty with every flip of the switch.

Sales:	Catalog Number:
Date:	Туре:
Model:	Notes:
Project:	OTCP
Rep:	we know light.™