

TCP's Selectable Commercial Recessed Downlights offer choices for color temperatures and wattages, making these adaptable for many situations.

Reasons to choose LED Selectable Commercial Recessed Downlights - Diffuser Version from TCP

- 3 selectable wattages
- Selectable colors (30K/35K/41K) or (27K/50K)
- 50,000 hour rated life minimizes replacement and maintenance costs
- Flicker-free design for consistent lighting
- Mounts directly to ceiling: 4, 6, 8, 10 or 12 inch
- Shatter resistant

- Easy installation and integrated trim
- Snap clips allow for installation without a recessed can
- 85° beam angle (4"/6"/8"/10")
- 70° beam angle (12")
- Smooth, uniform dimming 100 5%
- Matte silver and white finishes available

Ideal Applications

- Commercial
- Retail

- Industrial
- Healthcare

Specifications

Color Temperatures	(30K/35K/41K) or (27K/50K)
Wattage Options	4" (7/9/12W), 6" (8/10/15W),
8" (11/15/19W), 10" (18/23/30W),
	12" (18/23/30W)
Input Line Voltage	120-277V
	50/60Hz
	O-10V

Lamp Life (rated)	50,000 hours
Minimum Starting Temp	
Maximum Operating Temp	104°F/40°C
CRI	80

IC rated for direct contact with insulation

UL approved for damp locations













LED Selectable Commercial Recessed Downlights Diffuser Version

Specifications



Selectable Commercial Recessed Downlight Diffuser Version (30K,35K,41K)

LUMENS																
					LOW	ST WAT	TAGE	MIDD	LE WAT	TAGE	HIGH	EST WA	TTAGE			
ITEM #	DESCRIPTION	VOLTAGE	INCAND. WATTS	WATTAGE	30K	35K	41K	30K	35K	41K	30K	35K	41K	LPW	CRI	CASE QTY
4" Selectable Commercia	l Recessed	Downlig	jht – 6	5 Watt	Repl	acem	ent •	50,0	00 H	lour						
DLC4SWUZDCCT (Matte Silver Finish) DLC4SWUZDCCTW (White Finish)	LED 4" Comm Downlight CCT	120-277	65	7/9/12	675	695	690	870	900	895	1150	1200	1190	LW: 96.4/99.3/98.6 MW: 96.7/100/99.4 HW: 95.8/100/99	80	8
6" Selectable Commercia	l Recessed	Downlig	jht – 8	5 Watt	Repl	acem	ent •	50,0)00 H	lour						
DLC6SWUZDCCT (Matte Silver Finish) DLC6SWUZDCCTW (White Finish)	LED 6" Comm Downlight CCT	120-277	85	8/10/15	820	850	865	1030	1080	1095	1430	1530	1515	LW:103/106/108 MW:103/108/110 HW: 95/102/101	80	8
8" Selectable Commercia	l Recessed	Downlig	jht – 8	5 Watt	Repl	acem	ent •	50,0)00 F	lour						
DLC8SWUZDCCT (Matte Silver Finish) DLC8SWUZDCCTW (White Finish)	LED 8" Comm Downlight CCT	120-277	85	11/15/19	1270	1300	1305	1720	1705	1775	2085	2150	2085	LW:115.5/118.2/119 MW:115/113.7/118.3 HW:110/113.2/110	80	4
10" Selectable Commerc	ial Recessed	l Downl	ight –	100 W	itt R	eplac	emen	t • 5	0,00	0 Ho	υr					
DLC10SWUZDCCT (Matte Silver Finish) DLC10SWUZDCCTW (White Finish)	LED 10" Comm Downlight CCT	120-277	100	18/23/30	2100	2150	2150	2590	2660	2660	3205	3330	3305	LW:116.7/119.4/119.4 MW:112.6/115.7/115.7 HW:106.8/111/110.2	80	1
12" Selectable Commerc	ial Recessed	Downl	ight –	125 W	itt R	eplac	emen	t • 5	0,00	0 Ho	υr	,				
DLC12SWUZDCCT (Matte Silver Finish) DLC12SWUZDCCTW (White Finish)	LED 12" Comm Downlight CCT	120-277	125	18/23/30	2110	2160	2180	2650	2690	2690	3260	3380	3360	LW:117.2/120/121.1 MW:115.2/117/117 HW:108.7/112.7/112	80	1











LED Selectable Commercial Recessed Downlights Diffuser Version

Specifications

Selectable Commercial Recessed Downlight Diffuser Version (27K,50K)

							LUM	IENS	_				
					LOWEST	WATTAGE	MIDDLE	WATTAGE	HIGHEST	WATTAGE			
ITEM #	DESCRIPTION	VOLTAGE	INCAND. WATTS	WATTAGE	27K	50K	27K	50K	27K	50K	LPW	CRI	CASI QTY
4" Selectable Commercial	Recessed Downl	ight Dif	fuser \	ersion -	- 65 W	att Re	placer	nent •	50,00	0 Hour			
DLC4SWUZDCCT2 (Matte Silver Finish) DLC4SWUZDCCT2W (White Finish)	LED 4" Comm Downlight Diffuser CCT	120-277	65	7/9/12	700	<i>75</i> 0	900	1000	1200	1300	LW:100/107.1 MW:100/111.1 HW:100/108.3	80	8
6" Selectable Commercial	Recessed Downl	ight Dif	fuser \	ersion -	- 85 W	att Re	eplacen	nent •	50,00	0 Hour			
DLC6SWUZDCCT2 (Matte Silver Finish) DLC6SWUZDCCT2W (White Finish)	LED 6" Comm Downlight Diffuser CCT	120-277	85	8/10/15	700	750	1000	1050	1450	1500	LW: 87.5/93.8 MW:100/105 HW: 96.7/100	80	8
8" Selectable Commercial	Recessed Downl	ight Dif	fuser \	ersion -	- 85 W	att Re	placen	nent •	50,00	0 Hour			
DLC8SWUZDCCT2 (Matte Silver Finish) DLC8SWUZDCCT2W (White Finish)	LED 8" Comm Downlight Diffuser CCT	120-277	85	11/15/19	1200	1300	1600	1650	2000	2050	LW:109.1/118.2 MW:106.7/110 HW:105.3/107.9	80	4
10" Selectable Commercia	al Recessed Dow	nlight D	iffuser	Version	- 100	Watt	Repla	cement	• 50,	000 H	our		
DLC10SWUZDCCT2 (Matte Silver Finish) DLC10SWUZDCCT2W (White Finish)	LED 10" Comm Downlight Diffuser CCT	120-277	100	18/23/30	1800	1850	2250	2300	2850	2950	LW:100/102.8 MW: 97.8/100 HW: 95/98.3	80	1
12" Selectable Commercia	al Recessed Dow	nlight D	iffuser	Version	- 125	Watt	Repla	cement	• 50,	000 H	our		
DLC12SWUZDCCT2 (Matte Silver Finish) DLC12SWUZDCCT2W (White Finish)	LED 12" Comm Downlight Diffuser CCT	120-277	125	18/23/30	1800	1850	2250	2300	2850	2950	LW:100/102.8 MW: 97.8/100 HW: 95/98.3	80	1












LED Selectable Commercial Recessed Downlights Diffuser Version

Accessories

	PRODUCT	ITEM NUMBER	DESCRIPTION	DIMENSIONS
¥	H. C.	46INFRAMEKIT	4"/6" ADJUSTABLE FRAME KIT (Compatible with 4" and 6" downlights)	NA
		EMBACKUPCOMDL1	EMERGENCY BACKUP FOR 4" AND 6" SELECTABLE COMMERCIAL DOWNLIGHT	9.45" X 1.77" X 1.18"
		EMBACKUPCOMDL2	EMERGENCY BACKUP FOR 8", 10" AND 12" SELECTABLE COMMERCIAL DOWNLIGHT	12.9" X 2.6" X 2.2"

Dimensions

Α	В	С	Item Number
5"	6.2"	4.5"	DLC4SWUZDCCT / DLC4SWUZDCCT2 / DLC4SWUZDCCTW / DLC4SWUZDCCT2W
6.4"	7.8"	5.6"	DLC6SWUZDCCT / DLC6SWUZDCCT2 / DLC6SWUZDCCTW / DLC6SWUZDCCT2W
7.4"	9.2"	7.3"	DLC8SWUZDCCT / DLC8SWUZDCCT2 / DLC8SWUZDCCTW / DLC8SWUZDCCT2W
8.2"	10.9"	9"	DLC10SWUZDCCT / DLC10SWUZDCCT2 / DLC10SWUZDCCTW / DLC10SWUZDCCT2W
9.5"	13"	11"	DLC12SWUZDCCT / DLC12SWUZDCCT2 / DLC12SWUZDCCTW / DLC12SWUZDCCT2W



For the most up-to-date specs, please visit www.tcpi.com









TECHNOLOGY CAST IN A BEAUTIFUL LIGHT

For over 30 years, TCP has been designing, developing and delivering energy-efficient lighting into the market. Thanks to our cutting-edge technology and manufacturing expertise, we have shipped billions of high quality lighting products. With TCP, you can count on a lighting product that is designed to meet the needs of the market - that transforms your surroundings and envelopes you in warmth - lighting that generates beauty with every flip of the switch.

Sales:	Catalog Number:
Date:	Туре:
Model:	Notes:
Project:	OTCP
Rep:	we know light.™