



# NLS Sensors

## Product Specifications



Take control of your lighting with TCP's DLC Listed Network Lighting Control system. Controlling your fixtures has never been easier than through the TCP NLS application. TCP's NLS sensors utilize passive infrared sensor technology to provide occupancy, vacancy, and daylight harvesting features. The Bluetooth® Mesh network means that all of your features will be connected regardless of your network status. Do more with TCP's NLS Network Lighting Control system.

### Reasons to choose NLS Sensors from TCP

- Meets DLC 5.1 Networked Lighting Control System Standards
- Utilizes 5.0 Bluetooth® mesh network for localized lighting control with no internet connection requirements
- Monitor energy consumption in the app or online
- Utilize groups or zones to control multiple fixtures at one time
- Occupancy and Daylight Harvesting sensors for maximum energy savings

### Applicable Product Lines

Add the option "NLS" to the end of the parent item number to order the TCP NLS sensor.

- DT Series Panels with Selectable CCT
- Select Series TRV Volumetric Troffers
- Select Series HB High Bay
- QHB Series High Bay<sup>1</sup>
- Select Series GPS Strip
- MWR Series Modern Wrap Strip
- EUFO Series Round High Bay

<sup>1</sup> NLS Sensor only available for 2 foot QHB in the A2, A3, and A4 packages.

Not all versions of this product are qualified on the DLC QPL. To view our DLC qualified products, please consult the DLC Qualified Products List at [www.designlights.org/qpl](http://www.designlights.org/qpl).



## Specifications

### Troffer and Panel Sensor Specs:

Sensor Type: Passive Infrared  
 Input Voltage: 12VDC  
 Maximum Mounting Height: 12 Ft. (4m)  
 Operating Temperature: -20°C – 60°C  
 Wireless Standard: 5.0 Bluetooth® Mesh

### Wall Mounted Bluetooth Dimming Switch:

Sensor Type: No Sensor  
 Installation: Field Installed  
 Maximum Range: N/A  
 Wireless Standard: 5.0 Bluetooth® Mesh

### High Bay Sensor Specs:

Sensor Type: Passive Infrared  
 Input Voltage: 12VDC  
 Maximum Mounting Height: 40 Ft. (12m)  
 Operating Temperature: -20°C – 60°C  
 Wireless Standard: 5.0 Bluetooth® Mesh



Not all versions of this product are qualified on the DLC QPL. To view our DLC qualified products, please consult the DLC Qualified Products List at [www.designlights.org/qpl](http://www.designlights.org/qpl).



TCP®

325 Campus Dr. | Aurora, Ohio 44202 | P: 800-324-1496 | [tcp.com](http://tcp.com)

©TCP JUN 2025/WF557250



**RoHS**  
COMPLIANT

**5 YEAR**  
WARRANTY