

These energy efficient lamps are the perfect solution for replacing fluorescent PL lamps. Designed for use in commercial downlights, they are ideal for a variety of retail, office and hospitality applications.

Reasons to choose the LED Adjustable Shape PL lamps from TCP

- Electronic Ballast compatible or Bypass installation
- Over 50% of energy savings compared to fluorescent alternatives
- Long-life of 50,000 hours with a 5 year warranty
- Can be installed horizontally or vertically
- Dimmable with recommended 0-10v dimming ballast for best performance
- 90° adjustable head, extendable body, rotatable base

Ideal Applications

- Recessed downlights
- Track and display lights

- Sconces
- General lighting

Specifications:

Voltage	120v only (Type A or Type B)
Input Line Frequency	50/60Hz
	50,000 hours
Minimum Starting Temp	22°C
0 1	40°C

CRI	80
Beam Angle	110°
Power Factor	0.99
Base	G24q/GX24q







Specifications:



ITEM #	DESCRIPTION	VOLTAGE	WATTS	CFL BALLAST EQUIVALENT	LUMENS	ССТ	HOURS	CRI	MOL (inches)	DIA (inches)	BASE	WARRANTY YEARS	CASE QTY
Adjustable S	hape — Type A/B — I	Dimmable	e* • 5(0,000 Hou	rs								
			A/B		A/B								
LPLU42AB5027K	LED 21W PL ADJ BR30 27K	120v	21/19	32-42	1800/2100	2700K	50,000	80	6.1	3.6	G24q/GX24q	5	12
LPLU42AB50VVP	LED 21W PL ADJ BR30 35K	120v	21/19	32-42	1925/2200	3500K	50,000	80	6.1	3.6	G24q/GX24q	5	12
LPLU42AB5050K	LED 21W PL ADJ BR30 50K	120v	21/19	32-42	1925/2200	5000K	50,000	80	6.1	3.6	G24q/GX24q	5	12
Adjustable S	hape — Universal Vo	ltage – 1	Гуре А	/B — Dimn	nable* • 5	0,000 H	ours						
			A/B		A/B								
LAPL42AB5027K	LED 21W PL ADJ BR30 27K	120-277v	21/19	32-42	1800/2100	2700K	50,000	80	6.1	3.6	G24q/GX24q	5	12
LAPL42AB5030K	LED 21W PL ADJ BR30 30K	120-277v	21/19	32-42	1900/2200	3000K	50,000	80	6.1	3.6	G24q/GX24q	5	12
LAPL42AB5035K	LED 21W PL ADJ BR30 35K	120-277v	21/19	32-42	1925/2200	3500K	50,000	80	6.1	3.6	G24q/GX24q	5	12
LAPL42AB5041K	LED 21W PL ADJ BR30 41K	120-277v	21/19	32-42	1925/2200	4100K	50,000	80	6.1	3.6	G24q/GX24q	5	12
LAPL42AB5050K	LED 21W PL ADJ BR30 50K	120-277v	21/19	32-42	1925/2200	5000K	50,000	80	6.1	3.6	G24q/GX24q	5	12

Suitable for use in enclosed luminaires.

*0 - 10v Dimmable in Type A mode only. Not dimmable in Type B mode.

TECHNOLOGY CAST IN A BEAUTIFUL LIGHT

For over 30 years, TCP has been designing, developing and delivering energy-efficient lighting into the market. Thanks to our cutting-edge technology and manufacturing expertise, we have shipped billions of high quality lighting products. With TCP, you can count on a lighting product that is designed to meet the needs of the market - that transforms your surroundings and envelopes you in warmth - lighting that generates beauty with every flip of the switch.

Sales:	Catalog Number:
Date:	Туре:
Model:	Notes:
Project:	OTCP
Rep:	we know light.™