



LED PL Lamps

Type AB & B



These energy efficient lamps are the perfect solution for replacing fluorescent PL lamps. Designed for use in commercial downlights, they are ideal for a variety of retail, office and hospitality applications.

Reasons to choose the LED PL lamps from TCP

- Bypass installation eliminates ballast compatibility issues and provides higher LPW efficiency
- Vertical and horizontal application options
- Classic PL shapes offer omni-directional lighting options
- Horizontal shapes offer rotatable base to direct light where needed
- Superior energy efficiency compared to CFL PL technology, providing instant energy savings
- Built-in 120-277V driver for multi-volt bypass applications
- GX23 base compatibility
- G24d/GX24d/G24q/GX24q base compatibility
- Suitable for use in dry and damp locations
- Long-life ratings 25,000 - 50,000 hours
- 5 year warranty

Ideal Applications

- Recessed downlights
- Track and display lights
- Sconces
- General lighting

Specifications

Voltage 120-277V
Input Line Frequency..... 50/60HZ
Lamp Life (Rated) 25,000/50,000 hours
Minimum Starting Temp -22°C
Maximum Operating Temp..... 40°C

CRI 80
Beam Angle BR Shapes 110°
Base GX23, 2G11,
G24d/GX24d/G24q/GX24q

Approved for enclosed fixtures with minimum lamp compartment size 8" diameter x 11" height.

TCP®

325 Campus Dr. | Aurora, Ohio 44202 | P: 800-324-1496 | tcp.com



RoHS
COMPLIANT

5 YEAR
WARRANTY
*Based on 12 hours use per day

Specifications



Type B Lamps

ITEM #	DESCRIPTION	VOLTAGE	WATTS	CFL WATT EQUIVALENT	LUMENS	LPW	CCT	HOURS	CRI	MOL (inches)	DIA (inches)	BASE	CASE QTY
5W – Type B – Non-Dimmable • 25,000 Hours													
LPLU09B2527K	LED 5W 1U B 27K	120-277	5	5-7-9	500	100	2700K	25000	80	6.5	1.3	GX23	12
LPLU09B2530K	LED 5W 1U B 30K	120-277	5	5-7-9	550	110	3000K	25000	80	6.5	1.3	GX23	12
LPLU09B2535K	LED 5W 1U B 35K	120-277	5	5-7-9	550	110	3500K	25000	80	6.5	1.3	GX23	12
LPLU09B2541K	LED 5W 1U B 41K	120-277	5	5-7-9	550	110	4100K	25000	80	6.5	1.3	GX23	12
LPLU09B2550K	LED 5W 1U B 50K	120-277	5	5-7-9	550	110	5000K	25000	80	6.5	1.3	GX23	12
7W – Type B – Non-Dimmable • 25,000 Hours													
LPLU13B2527K	LED 7W 1U B 27K	120-277	7	9-13	700	100	2700K	25000	80	6.5	1.3	GX23	12
LPLU13B2530K	LED 7W 1U B 30K	120-277	7	9-13	750	107.1	3000K	25000	80	6.5	1.3	GX23	12
LPLU13B2535K	LED 7W 1U B 35K	120-277	7	9-13	750	107.1	3500K	25000	80	6.5	1.3	GX23	12
LPLU13B2541K	LED 7W 1U B 41K	120-277	7	9-13	750	107.1	4100K	25000	80	6.5	1.3	GX23	12
LPLU13B2550K	LED 7W 1U B 50K	120-277	7	9-13	750	107.1	5000K	25000	80	6.5	1.3	GX23	12
6W – Type B – Non-Dimmable • 25,000 Hours													
LPL209B2530K	LED 6W 2U B 30K	120-277	6	9-13	600	100	3000K	25000	80	4.6	1.3	G23 / GX23	12
8W – Type B – Non-Dimmable • 25,000 Hours													
LPL213B2527K	LED 8W 2U B 27K	120-277	8	9-13	1000	125	2700K	25000	80	5.9	1.3	G23 / GX23	12
LPL213B2530K	LED 8W 2U B 30K	120-277	8	9-13	1000	125	3000K	25000	80	5.9	1.3	G23 / GX23	12
LPL213B2535K	LED 8W 2U B 35K	120-277	8	9-13	1000	125	3500K	25000	80	5.9	1.3	G23 / GX23	12
LPL213B2541K	LED 8W 2U B 41K	120-277	8	9-13	1000	125	4100K	25000	80	5.9	1.3	G23 / GX23	12
LPL213B2550K	LED 8W 2U B 50K	120-277	8	9-13	1000	125	5000K	25000	80	5.9	1.3	G23 / GX23	12



LED PL Lamps

Type B Lamps (continued)

ITEM #	DESCRIPTION	VOLTAGE	WATTS	CFL WATT EQUIVALENT	LUMENS	LPW	CCT	HOURS	CRI	MOL (inches)	DIA (inches)	BASE	CASE QTY
8W – Type B – Non-Dimmable • 25,000 Hours PHASING OUT													
LPL218B2527K	LED 8W 2U B 27K	120-277	8	13-18-26	975	121.9	2700K	25000	80	5.7	1.1	G24d / GX24d / G24q / GX24q	12
LPL218B2530K	LED 8W 2U B 30K	120-277	8	13-18-26	1000	125	3000K	25000	80	5.7	1.1	G24d / GX24d / G24q / GX24q	12
LPL218B2535K	LED 8W 2U B 35K	120-277	8	13-18-26	1025	128.1	3500K	25000	80	5.7	1.1	G24d / GX24d / G24q / GX24q	12
LPL218B2541K	LED 8W 2U B 41K	120-277	8	13-18-26	1050	131.3	4100K	25000	80	5.7	1.1	G24d / GX24d / G24q / GX24q	12
LPL218B2550K	LED 8W 2U B 50K	120-277	8	13-18-26	1050	131.3	5000K	25000	80	5.7	1.1	G24d / GX24d / G24q / GX24q	12
13W – Type B – Non-Dimmable • 25,000 Hours PHASING OUT													
LPLU42B2527K	LED 13W 3U B 27K	120-277	13	32 - 42	1400	107.7	2700K	25000	80	5.5	1.8	G24d / GX24d / G24q / GX24q	12
LPLU42B2530K	LED 13W 3U B 30K	120-277	13	33 - 42	1500	115.4	3000K	25000	80	5.5	1.8	G24d / GX24d / G24q / GX24q	12
LPLU42B2535K	LED 13W 3U B 35K	120-277	13	34 - 42	1500	115.4	3500K	25000	80	5.5	1.8	G24d / GX24d / G24q / GX24q	12
LPLU42B2541K	LED 13W 3U B 41K	120-277	13	35 - 42	1600	123.1	4100K	25000	80	5.5	1.8	G24d / GX24d / G24q / GX24q	12
LPLU42B2550K	LED 13W 3U B 50K	120-277	13	36 - 42	1600	123.1	5000K	25000	80	5.5	1.8	G24d / GX24d / G24q / GX24q	12
9W – Type B – Non-Dimmable • 50,000 Hours PHASING OUT													
LPLH26B5027K	LED 9W HORIZ B 27K	120-277	9	18 - 26	1100	122.2	2700K	50000	80	5.6	1.4	G24d / GX24d / G24q / GX24q	12
LPLH26B5041K	LED 9W HORIZ B 41K	120-277	9	18 - 26	1150	127.8	4100K	50000	80	5.6	1.4	G24d / GX24d / G24q / GX24q	12
9W – Type B – Non-Dimmable • 50,000 Hours PHASING OUT													
LPLV26B5027K	LED 9W BR30 B 27K	120-277	9	18 - 26	1100	122.2	2700K	50000	80	5.2	3.7	G24d / GX24d / G24q / GX24q	12
LPLV26B5030K	LED 9W BR30 B 30K	120-277	9	18 - 26	1100	122.2	3000K	50000	80	5.2	3.7	G24d / GX24d / G24q / GX24q	12
LPLV26B5035K	LED 9W BR30 B 35K	120-277	9	18 - 26	1150	127.8	3500K	50000	80	5.2	3.7	G24d / GX24d / G24q / GX24q	12
LPLV26B5041K	LED 9W BR30 B 41K	120-277	9	18 - 26	1150	127.8	4100K	50000	80	5.2	3.7	G24d / GX24d / G24q / GX24q	12
LPLV26B5050K	LED 9W BR30 B 50K	120-277	9	18 - 26	1150	127.8	5000K	50000	80	5.2	3.7	G24d / GX24d / G24q / GX24q	12
17.5W – Type B – Non-Dimmable • 50,000 Hours PHASING OUT													
LPLU40B5027K	LED 17W PLL40 B 27K	120-277	17.5	40	2050	117.1	2700K	50000	80	21.1	1.7	2G11	30
LPLU40B5030K	LED 17W PLL40 B 30K	120-277	17.5	40	2050	117.1	3000K	50000	80	21.1	1.7	2G11	30
LPLU40B5035K	LED 17W PLL40 B 35K	120-277	17.5	40	2000	114.3	3500K	50000	80	21.1	1.7	2G11	30
LPLU40B5041K	LED 17W PLL40 B 41K	120-277	17.5	40	2100	120	4100K	50000	80	21.1	1.7	2G11	30
LPLU40B5050K	LED 17W PLL40 B 50K	120-277	17.5	40	2150	122.9	5000K	50000	80	21.1	1.7	2G11	30

Type AB Lamps

ITEM #	DESCRIPTION	VOLTAGE	WATTS	CFL WATT EQUIVALENT	LUMENS	LPW	CCT	HOURS	CRI	MOL (inches)	DIA (inches)	BASE	CASE QTY
24W – Type AB – Non-Dimmable • 50,000 Hours													
LUPLL24AB5CCTP	LED 24W LUPLL AB 5CCT	120	24	40	3200	133.3	30K/35K/40K/50K/65K	50000	80	21.1	1.7	2G11	30

Approved Emergency Battery Backups

Bodine	B50
IOTA	I-48 TBTS
TCP	20B50

TCP®

325 Campus Dr. | Aurora, Ohio 44202 | P: 800-324-1496 | tcp.com

©TCP SEP 2026/WF407600



RoHS
COMPLIANT

5 YEAR
WARRANTY
*Based on 12 hours
use per day

TECHNOLOGY CAST IN A BEAUTIFUL LIGHT

For over 30 years, TCP has been designing, developing and delivering energy-efficient lighting into the market. Thanks to our cutting-edge technology and manufacturing expertise, we have shipped billions of high quality lighting products. With TCP, you can count on a lighting product that is designed to meet the needs of the market - that transforms your surroundings and envelopes you in warmth - lighting that generates beauty with every flip of the switch.

Sales:

Date:

Model:

Project:

Rep:

Catalog Number:

Type:

Notes:



For more information on the quality and care TCP can deliver, call us at **800.324.1496** or visit tcpi.com

325 Campus Dr. | Aurora, Ohio 44202 | P: 800.324.1496 | F: 877.487.0516