



LED Multi-Pack Lamps

Product Specifications



For an affordable LED upgrade, switch to TCP Multi-Packs, available for dimmable and non-dimmable A-Lamps, BR30s and PAR38s. See how switching to LEDs can maximize savings and minimize maintenance costs.

Reasons to choose LED Multi-Packs from TCP

- Long-life: 15,000 hours minimizes replacement and maintenance costs (non-dim A19 - 10,000 hours)
- Inexpensive alternative for cost-sensitive projects
- ANSI Construction Compliant to fit most applications
- A-Lamps and BR30s are UL approved for damp locations when protected from the elements
- PAR38 lamps are UL approved for wet locations

Ideal Applications

- Commercial
- Industrial
- Retail
- Residential

Specifications

Input Line Voltage 120 VAC
Input Line Frequency..... 50/60HZ
Lamp Life (Rated) 10,000/15,000 hours
Minimum Starting Temp -22°F/-30°C

Maximum Operating Temp.....40°C
CRI..... 80
Warranty 1 year/3 years



LED Multi-Pack Lamps

Specifications



**Filament A-Lamps
Dimmable**



**A-Lamps
Non-Dimmable**



**A-Lamps
Dimmable**



**PAR38
Dimmable**

ITEM #	DESCRIPTION	PACK QTY	VOLTAGE	WATTS	LIFE	REPLACEMENT	LUMENS	LPW	BEAM ANGLE	CCT(K)	CRI	MOL (inches)	DIA (inches)	BASE	MASTER PACK
Filament A-Lamps Dimmable															
FA19D6027EVV4	LED 8V A19 FIL DIM 27K FR 4PK	4 PACK	120V	8	15000	60	800	100	OMNI	2700	80	4.2	2.3	E26	12
FA19D6030EVV4	LED 8V A19 FIL DIM 30K FR 4PK	4 PACK	120V	8	15000	60	800	100	OMNI	3000	80	4.2	2.3	E26	12
FA19D6041EVV4	LED 8V A19 FIL DIM 41K FR 4PK	4 PACK	120V	8	15000	60	800	100	OMNI	4100	80	4.2	2.3	E26	12
FA19D6050EVV4	LED 8V A19 FIL DIM 50K FR 4PK	4 PACK	120V	8	15000	60	800	100	OMNI	5000	80	4.2	2.3	E26	12
A-Lamps Non Dimmable															
L9A19N1041K4	LED 9.5W A19 ND 41K 4PK	4 PACK	120V	9.5	10000	60	800	88.9	OMNI	4100	80	4.3	2.4	E26	12
A-Lamps Dimmable															
L9A19D1527K4	LED 9W A19 DIM 27K 4PK	4 PACK	120V	9	15000	60	800	88.9	OMNI	2700	80	4.3	2.4	E26	12
L9A19D1530K4	LED 9W A19 DIM 30K 4PK	4 PACK	120V	9	15000	60	800	88.9	OMNI	3000	80	4.3	2.4	E26	12
L9A19D1541K4	LED 9W A19 DIM 41K 4PK	4 PACK	120V	9	15000	60	800	88.9	OMNI	4100	80	4.3	2.4	E26	12
L9A19D1550K4	LED 9W A19 DIM 50K 4PK	4 PACK	120V	9	15000	60	800	88.9	OMNI	5000	80	4.3	2.4	E26	12
Par38 Wet Location, Dimmable															
L90P38D15V30KFL2	LED 13W P38 DIM 30K FL 2PK	2 PACK	120V	13	15000	90	1100	84.6	40	3000	80	5.3	4.8	E26	12
L90P38D15V41KFL2	LED 13W P38 DIM 41K FL 2PK	2 PACK	120V	13	15000	90	1100	84.6	40	4100	80	5.3	4.8	E26	12

SUGGESTED DIMMER COMPATIBILITY	
MANUFACTURER	MODEL NUMBER
Leviton	R50-IPLO6-10M
	R61-06674-POI
Lutron	CTCL-153PDH-WH
	TGCL-153PH-WH
	DVVCL-153PH-WH

Note: E26 compatible dimmer

TCP®

325 Campus Dr. | Aurora, Ohio 44202 | P: 800-324-1496 | tcp.com

©TCP SEP 2026/WF207854



1 YEAR
WARRANTY*
10,000 HOUR LAMPS

3 YEAR
WARRANTY*
15,000 HOUR LAMPS

*Based on 12 hours
use per day

TECHNOLOGY CAST IN A BEAUTIFUL LIGHT

For over 30 years, TCP has been designing, developing and delivering energy-efficient lighting into the market. Thanks to our cutting-edge technology and manufacturing expertise, we have shipped billions of high quality lighting products. With TCP, you can count on a lighting product that is designed to meet the needs of the market - that transforms your surroundings and envelopes you in warmth - lighting that generates beauty with every flip of the switch.

Sales:

Date:

Model:

Project:

Rep:

Catalog Number:

Type:

Notes:



For more information on the quality and care TCP can deliver, call us at **800.324.1496** or visit tcpi.com

325 Campus Dr. | Aurora, Ohio 44202 | P: 800.324.1496 | F: 877.487.0516